

Procure



**Powered By Choice,
Driven By You.**

XM4000HS/G

Warranty

100% Credit: 0/1400

Technical specification

Power (W) - 4000
Rated Current (A.D.C.) - 135
Voltage (V.D.C.) - 30
Current Control Range (A.D.C.) - 80-150
Average Lumen Output (Lm) - 155000
Burning Position - H±20° V±20°
Forced Air Cooling (m/sec.) - 10-13
Anode (+) Base Ø - Pin Ø or Thread (mm) - 30-9.5
Cathode (-) Base Ø - Pin Ø or Thread (mm) - 30-7.9

Cross Reference

OSRAM - XBO 4000W/HS OFR
Christie - CXL-40SC
USHIO - UXL-40SC
Superior Quartz - SX42001

Projector Reference

NEC NC2500S
NEC NC3200S
NEC NC3240S 4kW
NEC NC3240S 7kW
L.P. ASSOCIATES 4KW Sky Dancer
L.P. ASSOCIATES 4KW XELAMP Architectural Spotlight
LYCIAN STAGE LIGHTING Lycian 1294 SuperArc 4K
PHOEBUS MANUFACTURING Silverbeam PSL-20 4K Xenon
PHOEBUS MANUFACTURING Silverbeam 360 4KW
SPACE CANNON ILLUMINATION 4.0kW
STRONG INTERNATIONAL Gladiator IV