

ANGEKIS

ASP-C-02



HD voice pickup range mic

high noise reduction, wide frequency response, sound balance, high fidelity, 10 meters pickup radius.

Efficient layout

Support mainstream education host, recorder interactive host, input and output independent volume control knob.

Compatible with common audio and video software

Support common education and conference SaaS software platform, such as: Skype for business, zoom.

The 3rd generation of Auctopus audio processing algorithm

24bit/48KHz sampling frequency Adaptive echo cancellation

Adaptive noise suppression Adaptive speech gain adjustment

Smart mixing

Specifications

ASP-C-02

Component

- digital audio processor
 - DSP processing bus structure
 - b-type USB connection
 - 2 road 3.81mm phoenix interface
 - input and output single adjustment knob
 - suspended spherical microphone
-

Color

- Matte black
-

Interface

- b-type USB interface
 - DC 12V power interface
 - 2 road 3.81mm phoenix interface
-

Power supply

- power adapter
 - input : 100-240V,0.5A,50/60Hz
 - output : DC 12V,2A
-

Computer system requirements

- Windows 7 / Windows 10 / Windows XP, MacOS
-

Suspended spherical microphone

- pick up radius: 10m Max
 - frequency response: 50hz-20khz
 - sensitivity :-47 plus or minus 3dB.
 - SNR: 75dB
-

Audio features

- adaptive echo cancellation
 - adaptive noise suppression
 - intelligent remix
-

Recommended conditions

- temperature: 20° ~ 70°
 - humidity:20~90%condensation free
 - noise level: < 48db
 - storage temperature: 20° ~ 70°
-

Product execution standard

- YD/T 993-1998
 - GB/T 9254-2008
 - GB 4843.1-2011
-

Audio processor

- frequency response(20hz-20khz@+4dBu)
 - microphone channel: +0/ -2db
 - line input channel: +0/-0.5dB.
 - Light
 - work normal: red, green alternatively lighting on
-

Certification

- CE;FCC;CCC
-

Warranty

- 3 years warranty
 - 1 year for battery guarantee
-



ASP-C-02