Procure



Powered By Choice, Driven By You.



Cleartalk ASP-10D-2

Conference Speakerphone

HD conference voice

32K sound pickup and 48K playback highly vocal;the sound is

The 3rd generation of Auctopus audio processing algorithm

360" high coverage, long pickup Upgrade full duplex technology.
The 384ms echo cancellation Dynamic noise reduction.



Two cascade omnidirectional microphones

Two omnidirectional microphones can pick up and play at the same time, the equipment does not interfere with each other

Perfect full-duplex

Two-way communication is more natural and smooth 5m voice pickup rang

Portable MIC and speaker

No driver required, plug and play; New appearance design, more suitable for various conference scenes

Cleartalk HD Daisy Chain

Architecture

- · Tabletop console contains audio processing functions ,USB function, indicator and touch key function
- · USB cable
- · USB extend line

Dimension

· 217*206*45mm

Net Weight

· 667g (single speakerphone)

Color

· Business Black

Interface

· USB 2.0 (compatible with USB 3.0)

Microphone

- · Omnidirectional microphone
- · Voice bandwidth:100-16KHz
- · Sensitivity: -38 dB 94dB SPL@1KHz

· SNR: 65dB

94dB SPL@1KHz, A-weight

Speaker

- ·2-inch anti-magnetic speakers
- ·4Ω5W
- ·100-24KHz

Power

- ·USB supply(DC 5V / 500mA)
- ·Built-in lithium battery

Audio

- ·384ms echo cancellation
- ·Dynamic noise reduction
- ·Full duplex
- ·360 degree pick-up range
- ·DSP audio processing

Computer system

·Windows 8 / Windows 7 / Windows 10/Windows XP,etc ·MAC 10.7 and above

Function

- ·support common computer softwares such as:
 - -Microsoft Teams
 - -Zoom
 - -etc
- ·microphone mute
- ·loudspeaker mute
- ·volume up/down
- ·indicator

Environmental requirements

Temperature: 5° -40° Humidity: 20 -85% (no condensation) Noise level: <48db

Storage temperature: -10° -40° Reverberation time: <0.5 seconds

Key

- ·microphone mute key
- ·loudspeaker mute key
- ·volume up/down keys

LED circle indicator

Green light always on:

working normally

Red light is always on:

the microphone is muted

A row of green lights at the

bottom: the speaker is muted

Red light flashes 3 times at the bottom: Connecting to charge

Green lights flashing at four

corners: normal standby

Red lights flashing at four corners:

low power indication

The green light at the bottom will flash 3 times every 5 minutes while charging

Long press the switch button at the bottom of the device for 3 seconds to switch on and off normally.

In standby mode, the device will automatically shut down after 20 minutes

Product execution standard

·YD/T 993-1998

·GB/T 9254-2008

·GB 4843.1-2011