

# Procure



**Powered By Choice,  
Driven By You.**



# ANGEKIS

## ASP-C-02

### HD voice pickup range mic

high noise reduction, wide frequency response, sound balance, high fidelity, 10 meters pickup radius.

### Efficient layout

Support mainstream education host, recorder interactive host, input and output independent volume control knob.

### Compatible with common audio and video software

Support common education and conference SaaS software platform, such as: Skype for business, zoom.

### The 3rd generation of Auctopus audio processing algorithm

24bit/48KHz sampling frequency Adaptive echo cancellation

Adaptive noise suppression Adaptive speech gain adjustment

Smart mixing

## ASP-C-02

### Component

- digital audio processor
  - DSP processing bus structure
  - b-type USB connection
  - 2 road 3.81mm phoenix interface
  - input and output single adjustment knob
- suspended spherical microphone

### Color

- Matte black

### Interface

- b-type USB interface
- DC 12V power interface
- 2 road 3.81mm phoenix interface

### Power supply

- power adapter
  - input : 100-240V,0.5A,50/60Hz
  - output : DC 12V,2A

### Computer system requirements

- Windows 7 / Windows 10 / Windows XP, MacOS

### Suspended spherical microphone

- pick up radius: 10m Max
- frequency response: 50hz-20khz
- sensitivity : -47 plus or minus 3dB.
- SNR: 75dB

### Audio features

- adaptive echo cancellation
- adaptive noise suppression
- intelligent remix

### Recommended conditions

- temperature: 20° ~ 70°
- humidity: 20~90% condensation free
- noise level: < 48db
- storage temperature: 20° ~ 70°

### Product execution standard

- YD/T 993-1998
- GB/T 9254-2008
- GB 4843.1-2011

### Audio processor

- frequency response (20hz-20khz@+4dBu)
  - microphone channel: +0/-2db
  - line input channel: +0/-0.5dB.
- Light
  - work normal: red, green alternatively lighting on

### Certification

- CE;FCC;CCC

### Warranty

- 3 years warranty
- 1 year for battery guarantee

