


# Procure



**Powered By Choice,  
Driven By You.**

# ClickShare C-10

Interactive wireless presentation for any meeting space



- **Interactive features: touchback, annotation and blackboarding**
- **Increased collaboration with 2 sources on screen**
- **Iconic ClickShare Button(s) for employees and guests**
- **100% secure, encrypted and cloud-managed**

ClickShare C-10 brings interactive wireless presentation to any meeting space. Content sharing is simple, with just one click on the ClickShare Button (Windows or Mac) or the ClickShare App (laptop, mobile or tablet). Start presenting within seconds: no cables, no software to download, no training needed.

## Product specifications

## CLICKSHARE C-10

### General specifications

Operating system	Windows 10 and higher macOS 11 (BigSur) and higher Android v9 and higher (ClickShare App)* iOS 12 and higher (ClickShare App)*
System requirements	For a smooth experience with Microsoft Teams or Zoom Minimum: Intel i3 dual-core processor or AMD Ryzen 7 / 8GB RAM / OS: Windows 10 latest build or Mac OS Mojave latest build Recommended: Intel i5 4-core processor or AMD Ryzen 9 / 8GB RAM / OS: Windows 11 latest build or Mac OS latest build
Video outputs	4K UHD (3840*2160) @ 30Hz, HDMI™ 1.4b or USB-C DisplayPort 1.2 (only Gen2)
Audio output	HDMI
USB	1 X USB-A, 1 X USB-C
ClickShare Buttons	1 or 2
ClickShare App	Desktop & Mobile
Native protocols	Airplay, Google Cast, Miracast*
Maximum sources simultaneously on screen	2
Noise Level	Max: 25dBA @ 0-30°C Max: 30dBA @ 30-40°C
Authentication protocol	WPA2-PSK in stand alone mode WPA2-PSK or IEEE 802.1X using the ClickShare Button in network integration mode
Wireless transmission protocol	IEEE 802.11 a/g/n/ac and IEEE 802.15.1
Reach	Adjustable with signal strength modulation; max: 30m (100 ft) between ClickShare Button and ClickShare Base Unit Frequency band 2.4 GHz and 5 GHz
Frequency band	2.4 GHz and 5 GHz (DFS channels supported in select number of countries)
Connections	1x Ethernet LAN 1Gbit 1x USB-C 2.0 (front); 1x USB-A 2.0 (front) -only Gen2; 1x USB-C 3.0 (front); 1x USB-A 3.0 (front)
Temperature range	Operating: 0°C to +40°C (+32°F to +104°F) Max: 35°C (95°F) at 3000m Storage: -20°C to +60°C (-4°F to +140°F)
Humidity	Storage: 0 to 90% relative humidity, non-condensing Operation: 0 to 85% relative humidity, non-condensing
Anti-theft system	Kensington lock
Certifications	FCC/CE
Touch screen support & Interactivity	Yes
Room Dock (peripheral support)	No
Local view	Yes
Network connection	LAN & WiFi
Management and reporting	Yes
Warranty	1 year standard. 5 years coverage upon registering via SmartCare
*	* depends on configuration, available in future firmware updates
<b>ClickShare Base Unit dimensions</b>	
Dimensions (HxWxD)	34 mm x 135 mm x 135 mm
Power consumption	Operational: 5-10W, 24W Max
Power supply	Operational: 5-10W, 24W Max
Weight	900 gr