

Procure



**Powered By Choice,
Driven By You.**

All Specifications

Display

Projection System	DLP Single 0.65" WXGA
Resolution	1280 x 800 pixels
Brightness (ANSI lumens)	4000 ANSI Lumens
Contrast Ratio (FOFO)	20000:1
Display Color	30 Bits (1,07 billion colors)
Native Aspect Ratio	Native 16:10 (5 aspect ratio selectable)
Light Source	Lamp
Light Source life*	Normal 6000 hr Economic 10000 hr SmartEco 10000 hr LampSave 15000hr
Resolution Support	VGA(640 x 480) to WUXGA_RB(1920 x 1200)

Optical

Throw Ratio	1.55~1.7 (87" ±3% @ 2.9m)
Zoom Ratio	1.1X
Lens shift	NA
Projection Offset**	100%±2.5% (Full-Height)
Projection Size	60"~150"
Keystone Correction	Auto 1D, Vertical +/- 40 degrees

Audio

Speaker	10W x 1
---------	---------

Special Feature

Security	Security Bar, Kensington lock
Feature	ID Auto Keystone, High Brightness, Spreadsheet mode, Bright Mode, Presentation Mode, Infographic Mode, Video Mode, Srgb Mode

Compatibility

Resolution Support	VGA(640 x 480) to WUXGA_RB(1920 x 1200)
Horizontal Frequency	15K~102KHz
Vertical Scan Rate	23 ~ 120 Hz
HDTV Compatibility	480i, 480p, 576i, 567p, 720p, 1080i, 1080p
Video Compatibility	NTSC, PAL, SECAM, SDTV (480i/576i), EDTV (480p/576p), HDTV (720p, 1080i/p 60Hz)

Connectivity

HDMI	HDMI-1 x1 HDMI-2 x1
PC (D-sub 15pin)	x1
Monitor out (D-sub 15pin,Female)	x1
Audio in (mini jack)	x1
Audio out (mini jack)	x1
RS232 In (D-sub 9pin, male)	x1
USB TypeA-1	x1 (1.5A power)
USB Type mini B	x1
IR Receiver (Front+Top)	x2
S-Video	x1
Composite Video (RCA)	x1

Power

Power Consumption(Max/Normal/Eco)	Max 280W, Normal 260W, Eco 215W
Standby Power Consumption	Normal < 0.5Watts.

Power Supply	100 ~ 240V AC
--------------	---------------

Dimension and Weight

Net Weight (Kg/ lbs)	2.3kg +/- 200g
Dimensions (W x H x D)(mm)	296 x 120 x 221 mm

Operation Condition

Noise Level(Normal/Eco)	34 /29 dBA
Operating Temperature	0~40°C

Accessories (Standard)

Remote Control w/ Battery	x 1 (5J.JND06.001)
Power Cord	x 1 (1.8m)
Warranty Card (by region)	x 1
VGA Cable	x 1 (1.5m)
AAA Battery	x2
QSG	x1 (4J.JND01.001)

Accessories (Optional)

Spare Lamp Kit	x 1 (5J.JND05.001)
Universal Ceiling Mount	x 1
3D Glasses	x 1 (5J.J9H25.002)
QCast Mirror dongle	x 1 (5A.JH328.10X)

OSD

OSD Language	Arabic/Bulgarian/ Croatian/ Czech/ Danish/ Dutch/ English/ Finnish/ French/ German/ Greek/ Hindi/ Hungarian/ Italian/ Indonesian/ Japanese/ Korean/ Norwegian/ Polish/ Portuguese/
--------------	---

Romanian/ Russian/ Simplified Chinese/Spanish/
Swedish/ Turkish/ Thai/ Traditional Chinese/
Farsi / Vietnamese/ (30 Languages)