

newline



GOOGLE CHROMEBOX OPS

powered by  **AOPEN**



Upgrade your interactive display experience with a **Chromebox OPS powered by AOPEN**, a compact yet powerful solution that seamlessly integrates with your **Newline panel**. Designed for effortless collaboration, engaging lessons, and impactful presentations, this **ChromeOS-powered device** transforms your interactive panel into a dynamic, all-in-one powerhouse.

With **plug-and-play simplicity**, the **Chromebox OPS** instantly connects to your Newline panel, ensuring a streamlined, hassle-free setup. Powered by ChromeOS, it delivers **lightning-fast performance, automatic updates, and built-in virus protection** for a secure and reliable experience. With **Google Play Store** support, you can install various apps to enhance functionality. With **seamless wireless casting**, you can share content from any device, making collaboration effortless. Plus, **remote device management** is simplified through the **Google Admin Console**, ensuring easy oversight of your entire **ChromeOS ecosystem**.

Perfect for **classrooms, boardrooms, and digital signage**, the **Chromebox OPS** enhances interactive learning with tools like **Google Classroom**, supports **virtual meetings with Google Meet, Zoom, and Microsoft Teams**, and powers **dynamic digital signage** for announcements or advertisements. Whether you're sketching, annotating, or collaborating in real-time, this device transforms your space into an engaging, connected environment.

newline

950 W Bethany Drive, Suite 330
Allen, TX 75013

Toll-Free: 888-233-0868
Local: 972-468-9728

sales@newline-interactive.com
www.newline-interactive.com

Google Chromebox OPS

OPS Details

SKU	CHRMOSOPS-AO
Used With:	C Series, Z Pro Series, Q Pro Series

Computer Specs

Operating System	ChromeOS
Dimensions (W x H x D)	7.87 x 4.69 x 1.18 inch
Weight	1.54 lb
CPU	Intel® Core i3-1315U Processor
Memory	8 GB DDR4
Storage	256 GB SSD
Graphics	Intel® UHD Graphics
Audio	3.5 Audio Jack x 1 (Combo)
LAN	Giga LAN x 1, 10/100/1000 Mbps
Wi-Fi & Bluetooth	WiFi 6E 802.11 b/g/n/ac/ax + BT 5.2
Front Panel I/O	USB 2.0 x 2; USB 3.2 x 2; USB Type-C x 1; HDMI 2.0 x 1; Dual band antenna x 2; Audio Jack (Combo) x 1, Power Button with LED indicator x 1, GbE LAN RJ45 x 1, Recovery button x 1, Kensington slot x 1
Rear Panel I/O	USB 3.2 x 1; USB 2.0 x 2; HDMI 2.0 x 2
Input Voltage	DC 12V ~ 19V
MTBF	50,000 hrs
Operating Temperature	0°C ~ 40°C (32°F ~ 104°F)
Storage Temperature	-20°C ~ 60°C (-4°F ~ 140°F)
Relative Humidity	93% RH max