

Procure



**Powered By Choice,
Driven By You.**

CP2215

Small-screen auditoriums | Boutique cinema | Post production | Screening rooms

Lowest upfront investment for DCI-compliant cinema on screens up to 58 feet wide



Key features:

- › **Easy to operate** – touch panel, or web-based GUI. Intelligent lens system (ILS™) for fast-set-up
- › **Easy to install** – lightweight all-in-one chassis for flexible mounting
- › **Easy to maintain** – rear access lamp change
- › **Affordable performance** – Christie Xenolite long-life, lower power-consumption lamps
- › **Reliability** – split power operation for use with UPS
- › **Compatibility** – works with Christie and 3rd-party IMBs, accessories and lenses

CHRISTIE XENOLITE

Industry's longest warrantied and most reliable lamps - 99.999% uptime

DIGITAL CINEMA CONFIGURATOR

Help find the right lamp for your projector on our website



christiedigital.com/cinema

Innovation in every frame™

Specifications


Christie CP2215

Brightness¹	nominal	• 15,000 lumens
	screen size	• 58" screen ¹
	lamp	• 1.4kW (CDXL-14M) 003-003066-01 • 1.6kW (CDXL-16M) 003-003900-01 • 1.8kW (CDXL-18SD) 003-0027420-01 • 2.0kW (CDXL-20SD) 003-001976-01 • 2.3kW (CDXL-23S) 003-004769-01
Contrast ratio		• 2000:1 full field on/off
Supported frame rates		• 2D up to 120 fps • 3D up to 60 fps/eye
Digital micromirror device		• 0.98" 2K 3-chip DMD DLP Cinema® • 2048 x 1080 pixels (2K)
Number of colors		• 35.2 trillion
Lens mount configuration		• Fully motorized Intelligent Lens System (ILS™)
Lenses		• 1.05:1 / 1.20-1.75:1 / 1.39-1.90:1 / 1.50-2.20:1 / 1.75-2.40:1 / 1.90-3.0:1 / 2.40-3.90:1
Power input requirements		• Main input: 200-240VAC 50-60Hz, 16A max • UPS input: 100-240VAC @ 50-60Hz, 10A max
Power consumption		• 3200W max
Lamp power supply		• 0.7kW - 2.3kW low-ripple switch mode power supply
Weight		• As installed: 122lbs max (55kg)
Dimensions (LxWxH)		• 27 x 26 x 15" (687 x 665 x 395mm)
Accessories		• 90 degree extraction duct adapter • Rack mount stand • Link Decryptor


¹ Maximum screen size depends upon various factors such as screen gain, lamp age, geometry, etc. Consult your Christie representative for detailed analysis. Measured at screen center.

Supports 3rd party IMB models from Dolby, GDC and others. Please contact Christie for updated compatability list.


Front view




Side view



Top view



Side view



Corporate offices

Christie Digital Systems USA, Inc.
Cypress
PH: +1 714-236-8610
Christie Digital Systems Canada
Inc.
Kitchener
PH: +1 519-744-8005

Worldwide offices

Australia
PH: +61 (0) 7 3624 4888
Brazil
PH: +55 11 3181-2952
China (Beijing)
PH: +86 10 6561 0240
China (Shanghai)
PH: +86 21 6030 0500

China (Shenzhen)
PH: +86 755 3680 7000
Colombia
PH: +57 (315) 652-9620
Germany
PH: +49 221 99 512-0
India
PH: +91 (080) 6708 9999

Mexico
PH: +52 (55) 4744-1791
Singapore
PH: +65 6877 8737
South Korea
PH: +82 2 702 1601
Spain
PH: +34 (0) 91 633 99 90

United Arab Emirates
PH: +971 (0) 4 503 6800
United Kingdom
PH: +44 (0) 118 977 8000
United States (Arizona)
PH: +1 602-943-5700
United States (Texas)
PH: +1 469-757-4420