



1717L 17-inch LCD

Touchscreen Monitor



Integrated Touch



Commercial Grade



HDMI

Product Overview

The Elo 1717L 17-inch standard aspect touchscreen monitor is built to withstand the rigors of continuous public use with a rugged built-for-touch design. Its stylish, thin and modern look, coupled with a retail-focused feature set makes it an attractive solution for commercial touchscreen monitor needs. The 1717L is well suited for point-of-sale, point-of-information, point-of-service, interactive signage and loyalty systems.

The 17-inch touchscreen offers multiple mounting options to ensure installation flexibility including: wall- and pole-mount via standard VESA mount patterns as well as tabletop accommodations with the use of the desktop stand. Capped through-mount holes on the base of the touchmonitor ensure table-top security.

Available touch technologies:

- TouchPro® PCAP
- AccuTouch® Resistive
- IntelliTouch® SAW

Customize with an integrated 3-track magnetic stripe reader (MSR)

Desktop, wall or VESA mounting

1717L 17-inch LCD Touchscreen Monitor

Specifications	
Model	1717L
Color	Black
Active Display Area	13.3" x 10.64" / 337.92 mm x 270.34 mm
LCD Technology	Active matrix TFT LCD with LED backlighting
Diagonal Size	17.0" / 431.8 mm
Aspect Ratio	5:4
Native (Optimal) Resolution	1280 x 1024
Other Supported Resolutions	640 x 480 @ 60Hz, 75Hz; 720 x 400 @ 70Hz; 800 x 600 @ 56Hz, 60Hz, 75Hz; 1024 x 768, @ 60Hz, 75Hz; 1280 x 1024 @ 60Hz, 75Hz
Number of Colors	16.7 million
Number of Touches	IntelliTouch & AccuTouch: Single-touch TouchPro PCAP: 10-touch
Brightness (typical)	LCD Panel: 250 nits TouchPro PCAP: 225 nits AccuTouch: 200 nits IntelliTouch: 225 nits
Response Time - Total (typical)	20 msec
Viewing Angle (typical)	Horizontal: +/-85° or 170° total; Vertical: +/-80° or 160° total
Contrast Ratio (typical)	1000:1
On-Screen Display (OSD)	Accessible through switches along the bottom. Controls: Menu, Up, Down, Select, Power Settings: Auto Adjust, Brightness, Contrast, H-position, V-position, Clock, Phase, Color Temperature, OSD Timeout, OSD Language, Sharpness, Recall Defaults, Information Languages: English, French, Italian, German, Spanish, Simplified Chinese, Traditional Chinese, Japanese Lockouts: OSD, Power
I/O Ports	VGA, HDMI, DC jack, AC jack, USB Type B, RS-232 (DB-9)
Video	Analog VGA on Female DB-15 connector, Digital HDMI on Type A receptacle Input Video Horizontal Sync frequency range: 31.5-80KHz, Input Video Vertical Sync (frame rate) frequency range: 56-75Hz
Power	Monitor AC input power connector: IEC 60320 C6 Monitor AC input voltage specifications: 100-240VAC, 50/60Hz. Monitor DC input power connector: Coaxial power jack (2.0mm pin outer diameter, 6.4mm barrel inner diameter) Monitor DC input voltage specifications: 12VDC +/- 5%
Power Consumption (typical)	Monitor only - ON: 11.5W (100% brightness); ON: 10W (default 80% brightness); SLEEP: 1.4W; OFF: 0.3W
Dimensions	With Stand: 15.43" x 8.48" x 14.24" / 391.9 mm x 215.4 mm x 361.6 mm Without Stand (Bezel): 15.4" x 2.15" x 14.2" / 392.0 mm x 54.5 mm x 361.6 mm Without Stand (Zero Bezel): 15.4" x 1.91" x 14.2" / 392.0 mm x 48.6 mm x 361.6 mm
Shipping Box Dimensions	20.12" x 9.17" x 20.08" / 511 mm x 233 mm x 510 mm
Weight	Unpackaged: 11.9 lbs / 5.4 kg; Packaged: 18.3 lbs / 8.3 kg
Mounting Options	VESA 4-hole 75mm mounting interface on rear of unit 3-hole threaded mounting on bottom of stand
Temperature	Operating: 0 °C to 40 °C / 32 °F to 104 °F; Storage: -20 °C to 60 °C / -4 °F to 140 °F
Humidity (non-condensing)	Operating: 20%-80%; Storage: 10%-95%
Regulatory Approvals and Declarations	Argentina S-mark; Australia RCM; Canada cUL, IC; China CCC; Europe CE; United Kingdom UKCA; Japan VCCI; Korea KCC, e-Standby; Mexico NOM; Taiwan BSMI Mark; United States UL, FCC; International CB; RoHS, China RoHS, WEEE
Warranty	3 years standard
Extended Warranty Options	4 year warranty coverage - Elo P/N: E898247 5 year warranty coverage - Elo P/N: E898449 3 year warranty coverage + AUR - Elo P/N: E898648 4 year warranty coverage + AUR - Elo P/N: E894921 5 year warranty coverage + AUR - Elo P/N: E895125
MTBF	50,000 hours demonstrated
What's in the Box	1717L, QIG, VGA cable (DB-15 male to DB-15 male), USB cable (USB Type A plug to USB Type B plug), Power cable - IEC 60320-C5 to NA/EU plug, stand base assembly, filler plate, HDMI cable

Ordering Information

Part Number	Technology	Surface Treatment	Interface	Bezel
E877820	AccuTouch	Antiglare	USB/Serial combo	Yes
E649473	AccuTouch ZB	Antiglare	USB/Serial combo	No
E077464	IntelliTouch	Antiglare	USB/Serial combo	Yes
E179069	IntelliTouch ZB	Clear	USB/Serial combo	No
E017030	IntelliTouch ZB	Antiglare	USB/Serial combo	No
E596951	TouchPro PCAP	Antiglare	USB/Serial combo	No

Learn more about Elo at [EloTouch.com](https://www.elotouch.com).

Americas

Tel +1 408 597 8000
elosales.na@elotouch.com

Europe (EMEA)

Tel +32 16 930 136
EMEA.Sales@elotouch.com

Asia Pacific

Tel +86 (21) 3329 1385
Elo.Asia@elotouch.com

Elo reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. Elo, the Elo logo, AccuTouch, IntelliTouch and TouchPro are either trademarks or registered trademarks of Elo Touch Solutions, Inc. All other trademarks are the property of their respective owners. © 2025 Elo Touch Solutions, Inc. All rights reserved. 25071AES00007

