

Procure



**Powered By Choice,
Driven By You.**

DS-D6122TH-B/C


Classroom Information Release Screen



- 1920 × 1080P@60 Hz full HD, 10-point capacitive touch, and 8-millisecond rapid response
- 27-millimeter-thick body with anti-glare toughened glass, preventing strong light interference and violent destruction
- Built-in light sensor module helps automatically adjust screen brightness to match surrounding lighting conditions, displaying clear pictures with energy saved
- Built-in 2 MP WDR camera captures clear images when facing against the light
- Recognize up to 5 persons in one second, meeting the requirements of quick attendance check for elective class
- Built-in omnidirectional microphone picks up sound within a radius of at least one meter
- Control access control devices through Wiegand protocol, and door locks with relays
- Built-in 13.56 MHz RFID card-swiping module with high response speed, compatible with the standard card of type A and B

▪ Specification

Model		DS-D6122TH-B/C
Product Model	Product Model	DS-D6122TH-B/C
Display	Viewing Angle	178°(V)/178°(H)
	Screen Size	21.5 inch
	Active Display Area	476.06 mm (H) × 267.79 mm (V)
	Backlight	TFT-LCD
	Resolution	1920 × 1080
	Brightness	600 cd/m ²
	Color Depth	8 bit
	Contrast Ratio	≥ 1000:1
	Response Time	≤ 14 ms
	Color Gamut	72%
	Reliability	7 × 16 h
Built-in System	Operation System	Android 6.0.1
	CPU	Cortex-A17, 4 Cores, 1.6 GHz
	Memory	2 GB
	Built-in Storage	16 GB EMMC
Smart	Lens	2 MP WDR Camera
	Face Database	20,000 pictures, JPG format allowed
	Face Detection Distance	Up to 5 m (196.86") 0.3 m to 1.5 m (11.81" to 59.06") recommended Adjustable through software
	Face Verification Accuracy	> 99%
	Face Verification Time	≤ 0.5 s/person
Touch	Touch Type	Capacitive touch
	Glass	3 mm anti-glare toughened glass
	Touch Point	10
Interface	Network Interface	LAN × 1, built-in Wi-Fi
	Data Transmission Interface	USB 2.0 × 2, BT 4.0 × 1, Card-swiping for IC card, Access control linkage
Internal Function	Loudspeaker	Built-in Speaker × 2
Power	Standby Consumption	≤ 0.5 W
	Power Consumption	≤ 40 W
Working Environment	Working Temperature	0 °C to 40 °C (30 °F to 104 °F)
	Working Humidity	10% to 90%
General	Product Dimensions (W × H × D)	518.26 mm × 359.99 mm × 27 mm (20.40" × 14.17" × 1.06") (without wall-mounted backboard)



		518.26 mm × 359.99 mm × 28.3 mm (20.40" × 14.17" × 1.11") (with wall-mounted backboard)
	Package Dimensions (W × H × D)	660 mm × 584 mm × 113 mm (25.98" × 22.99" × 4.45")
	Net Weight	7.18 kg (15.83 lb)
	Gross Weight	8.32 kg (18.34 lb)
	Packing List	21.5-inch digital signage × 1, L-shaped T10 wrench × 1, power cord × 1, power adapter × 1, torx screw for security × 2, package of mounting bolts × 2, quick start guide × 1

▪ **Available Model**

DS-D6122TH-B/C

▪ Dimension

