

Procure



**Powered By Choice,
Driven By You.**

JTOUCH SERIES 00 - INF6500



Flagship Product Line, Breakthrough Performance.

Cutting-edge technology at a competitive price point. For a more connected and engaging collaboration experience in class and meeting rooms. InFocus JTouch 50 Series offers ease of use bringing capability to the room without complexity for a proven return on your technology investment. It is simple to deploy and support, leading to a lower total cost of ownership.

Designed and built with 2nd generation zero bonding technology and 3mm hardened anti-glare glass. Elegant narrow two-tone bezels, concealed snap-in wireless module, magnetic pen holders, and stereo 20-watt speakers all provide an outstanding crystal clear audio-visual and multi-touch experience more significant than ever before.

Our most advanced JTouch running Android 9 is controlled by the MediaTek 9950 SoC with the ARM Cortex™ A73 Quad Core 1.8Ghz. This powerful combination increases the computing performance up to 68% and delivers flawless 4K video performance.

Features & Benefits

CASTING & COLLABORATION WITH LIGHTCAST 3 & WIFI 6

The dual-band MU-MIMO wireless module provides the latest WiFi-6 standard supporting multiple device connections, reduced latency, and throughput speeds of up to 9.6 Gigabits per second. This latest technology provides the base connection for seamless casting and collaboration capabilities of the LightCast3™ software for meetings over a local network or via the JTouch hotspot for additional security.

USB-C A SINGLE CABLE SOLUTION

Easily connect USB-C devices through the 50 series's USB-C port with up to 65-watt power delivery. USB-C supports video, audio, touch, data, and power output for charging laptop devices quickly over a single cable.

LIGHTMANAGER™ & LIGHTSTORE™

Users can easily search for and install from a curated selection of apps in the InFocus LightStore or use the built-in Cloud Drive app for accessing documents on OneDrive™ or Google Drive™. Creative meetings and classroom lessons are enhanced with annotation anywhere, viewing Office files, creating whiteboards, and so much more. Administrators can use the InFocus LightManager software to manage the deployment of apps, release firmware updates, deploy settings, and schedule alert messages all remotely.

RUN ANDROID OR MICROSOFT

All the flexibility you need our powerful and flexible computing modules to give you the freedom to choose the interactive display operating system that works best for your daily needs and IT ecosystem. Intel Core™ i5 & i7 10th Gen available for the INF6550, INF7550, and INF8650. Intel Core™ i5 & i7 11th Gen for the INF9850. Intel Core™ i5 10th Gen-10400, 8GB Memory, 32GB SSD, 21.5\"/>

By clicking "Accept All Cookies", you agree to the storing of cookies on your device to enhance site navigation, analyze site usage, and assist in our marketing efforts.

SENSITIVE, THOUGHTFUL DESIGN

Designed and built with 2nd generation zero bonding technology, eliminates reflection between the screen glass and LCD cell resulting in improved contrast, higher levels of brightness, and responsive touch for a smooth and intuitive writing experience. The 3mm hardened anti-glare glass, elegant narrow lightweight two-tone bezels, concealed snap-in wireless module, magnetic pen holders, and stereo 20-watt speakers all provide an outstanding crystal clear audio-visual and multi-touch experience more significant than ever before.








BREAKTHROUGH PERFORMANCE

Our most advanced JTouch is controlled by the MediaTek 9950 SoC with the ARM Cortex™ A73 Quad Core 1.8Ghz. This powerful combination increases the computing performance up to 68% over earlier generations and delivers flawless 4K video performance.

Display

Screen Size (Diagonal)	65"
Backlight	D-LED
Native Resolution	4K
Pixels	3840 x 2160
Aspect Ratio	16:9
Contrast Ratio	1200:1
Dynamic Contrast Ratio	5000:1
Brightness (Maximum cd/m2)	450
Response Time (ms)	6
Display Colours (billion)	1.07
Refresh Rate (Hz)	60
Viewing Angle (H-V°)	178 / 178
Viewable Area (mm / in)	1428 x 804 / 56 x 3
Glass Treatment (mohs)	Anti Glare 7
Glass Thickness (mm)	4
Sensors	-
Audio (w)	2 x 15
Lifetime Maximum (hrs)	30000
Frame Material	Metal

Connectivity

Inputs	
VGA	
3.5 mm AV	
YPbPr	
HDMI™ 2.0	  
DP 1.2	
USB-A 2.0	   
3.5 mm Stereo Mini Jack	
RJ45	
Outputs	
3.5 mm AV	

By clicking “Accept All Cookies”, you agree to the storing of cookies on your device to enhance site navigation, analyze site usage, and assist in our marketing efforts.

3.5 mm Stereo Mini Jack	✓
RJ45	✓
Other	
RS232	✓
Remote Control	✓
Open Pluggable Specification (OPS) Slot	✓
Power	
Power Supply (V / Hz)	AC 100 - 240, 50/60
Power Consumption Max[W]	140
Power Consumption Network Standby (W)	<2.0
Power Consumption Standby (W)	<0.5
Touch System	
Touch Technology	Infrared
Touch Points Maximum	20
Typical Response Time (ms)	≤10
Accuracy (mm)	±,1
Minimum Object Size Single Touch (mm)	>3
Minimum Object Size Multi Touch (mm)	>8
Windows, Linux, Mac OS, Chrome Support	✓
Embedded System	
Operating System & Version	Android 8
System on Chip (SoC)	MSD8386
Central Processing Unit (CPU)	ARM® Cortex™ Dual core A73 + ARM® Cortex™ Dual core A53
Graphics Processing Unit (GPU)	ARM® Quad Core Mali-G51
Random Access Memory (RAM) GB	32
Read Only Memory (ROM) GB	3
Included Applications	LightCast, Whiteboard, Browser, Finder, LightCast2, Annotation, WPS Viewer, Stopwatch, Calculator, Screen Capture, Countdown
Optional Upgrades	
Intel® Core™ i3 Slot-In PC/OPS	✓
Intel® Core™ i5 Slot-In PC/OPS	✓
Intel® Core™ i7 Slot-In PC/OPS	✓
General	
Dimensions (L x W x H) [mm / in]	1506 x 96 x 901 / 59.3 x 3.8 x 35.5
Weight [kg / lb]	42 / 92.6
Shipping Dimensions (L x W x H) [mm / in]	1660 x 245 x 1045 / 65.3 x 9.65 x 41.1
Shipping Weight [kg / lb]	57 / 125.7
Mounting VESA MIS-F	600 x 400
Operating Temperature [°C / F]	0 ~ 40 / 32 ~104
Operating Humidity [%]	10 ~ 90

By clicking "Accept All Cookies", you agree to the storing of cookies on your device to enhance site navigation, analyze site usage, and assist in our marketing efforts.

Storage Humidity [%]	10 ~ 90
Security	PIN, Kensington Lock
In the Box	Remote Control (no batteries), 2x Sylum, Power Cord, 3m USB A to B, 3m HDMI, QSG, WiFi Module
Safety and Regulatory	CB, CE EMC, IC, FCC, cTUVus, NOM, EAC, BIS
Environmental	RoHS, WEEE, EU Energy

Copyright © 2022, InFocus and its logo is a registered trademark of InFocus Corporation. Maxnerva Technology Services Limited is the licensee of the registered trademark. All other product names and company names used herein are for identification purposes only and may be trademarks or registered trademarks of their respective owners. Errors and omissions excepted; all specifications are subject to change without notice. All images are for representation purposes only and may be simulated.

By clicking “Accept All Cookies”, you agree to the storing of cookies on your device to enhance site navigation, analyze site usage, and assist in our marketing efforts.