

**Video Conferencing Solution
for mid- to large-sized meeting
rooms and conference halls**

**Prestigio
SOLUTIONS**



4K PTZ CAMERA ALPHA

Professional quality

Advanced camera specifications based on Sony Sensor allow to stream video in 4K UHD resolution at 60 fps, providing unsurpassed image quality and maximum realism.

AI intelligent tracking

Camera-integrated smart tracking algorithm ensures participants' instant detection and presenters' smooth automatic tracking & framing.

Convenient connection

The 4K PTZ Camera Alpha is equipped with multiple ports (Ethernet, USB, HDMI, 3G-SDI) for the multiple choice of the camera's connection to the wide range of modern devices.

Power over Ethernet

Thanks to the PoE support, you can place the camera anywhere, such as on the wall, with no need for direct access to a power outlet.

4K PTZ CAMERA ALPHA

PSVCCU8N002

Prestigio
SOLUTIONS




Video Conferencing camera for mid- to large-sized meeting rooms and conference halls.



AI Intelligent tracking



4K UHD



Sony Sensor



Rotation range
(Horizontal/Vertical)
 $\pm 170^\circ$ / $-30^\circ \sim +90^\circ$



16x digital zoom
and 12x optical



Noise suppression
and echo cancellation



Plug & Play Technology,
PoE function support

VIDEO SYSTEM	4K (60fps)
SENSOR NATIVE RESOLUTION	8.4M
SENSOR TYPE	1/2.8" SONY high quality UHD CMOS sensor
OUTPUT FORMAT	MJPEG/YUY2/H.264
FIELD OF VIEW (HORIZONTAL/VERTICAL)	80.8° ~ 7.5° / 49.9° ~ 4.3°
ROTATION RANGE (HORIZONTAL/VERTICAL)	$\pm 170^\circ$ (with tolerance 6%) / $-30^\circ \sim +90^\circ$ (with tolerance 6%)
LENS	12x, f = 3.47mm ~41.65mm, F 1.84 ~ F 3.72
DIGITAL ZOOM	16x
DIGITAL NOISE REDUCTION	2D & 3D digital noise reduction
AI INTELLIGENT TRACKING	Supported
SUPPORT PROTOCOLS	NDI® HX, TCP/IP, HTTP, RTSP, RTMP, ONVIF, DHCP, MULTICAST
INTERFACES	HDMI OUT 2.0, 3G-SDI OUT, LINE IN, RS485, USB 3.0 (Type C), RS232 OUT, RS232 IN, LAN (PoE+), JEITA type (DC IN 12V)
OPERATING SYSTEMS	Windows 7, Windows 8, Windows 10, Windows 11, Mac OS X, Linux, Android
DIMENSIONS (L x H x D), MM	223 x 166.4 x 163
WEIGHT (NET/GROSS), KG	1.8 / 4.7
IN THE BOX	Power adapter, EU power cable, UK power cable, USB Type A/C cable, RS232 cable, lens cover, remote control unit, wall mount kit, tripod screw, quick start guide, warranty card