# Procure



Powered By Choice, Driven By You.

## SAMSUNG

# Small spaces hold sizable opportunities

Get the most out of every space with Samsung QBR series small digital signage. Full HD resolution means every message will be sharp and crystal-clear, making these brilliant displays ideal for retail environments, meeting rooms and public spaces. An embedded media player (SoC) lets you easily display content with no external PC required. And for added functionality, the QBR-T/QBR-TB series feature embedded touch screens.



#### Small size with full functionality

Slim designs allow for use in compact locations. A sleek back design makes them ideal as freestanding or wall-mounted displays.



#### Powerful all-in-one digital signage solution

With the embedded media player, there's no separate PC required, no extra mounting or cabling, and no additional external hardware requiring maintenance. Just plug in the displays and go.



#### Crisp and visible content

The 24" models feature a non-glare panel, for easy-to-read content in any ambient light.



#### Robust content management and monitoring

Our leading-edge digital signage platform makes content management easier, more flexible and more robust. Use the data capture tools to inform content creation and automated, targeted distribution. Easily create content with included templates. And manage it all from a single source (license required).

samsung.com/display



#### Built-in Wi-Fi

Built-in Wi-Fi allows wireless remote management of both content and display. Eliminating LAN cables simplifies installation.



#### IP5X for lasting durability

IP5X rating ensures efficient and reliable performance even in dusty environments and public spaces, which reduces overall cost of operation.



#### Embedded touch screen (QBR-T/ OBR-TB series)

Touch screens increase your possibilities. With 10-point multi-touch capability, they can improve interaction, engagement, satisfaction and sales.



#### Pivot to landscape or portrait

QBR series small signage displays fit your space. They can display your content in landscape or portrait mode.



#### Reliable operation and 3-year warranty

QBR series small signage displays are engineered for dependable 16/7 operation. And a 3-year limited warranty offers further peace of mind.

# **QBR Series Small Digital Signage**













# **QBR Series Small Digital Signage**

		QB13R-B	QB13R-T	QB24R-B	QB24R-TB
	Diagonal Size Class	1,			24"
Panel	Panel Type Measured	13. Edge	LED		23.8" ADS
	Touch Screen	No	Yes	No	Yes
	Resolution	FHD (192	0 x 1080)		920 x 1080) 5 x 0.2745
	Pixel Pitch (mm)	0.153 :	¢ 0.153	0.274	5 x 0.2745
	Active Display Area		x 165.24 (V)		I) x 296.46 (V)
	Brightness (Typ.)	300 nits 800:1	300 nits (w/o Glass) 600:1	250 nits 1000:1	250 nits (w/o Glass) 1000:1 (w/o Glass)
	Contrast Ratio (Typ.)	800·1			*/178*
	Viewing Angle (H / V) Response Time (G-to-G)	8ms	(Typ.)	140	ns (Typ.) 6-bit, Dither 8-bit)
	Display Colors	sponse Time (G-to-G) Splay Colors Splay Colors Sense Time (G-to-G) Sense Time (G-to-G) Sense Time (G-to-G)		16.7 M (Real	5-bit, Dither 8-bit)
	Display Colors Color Gamut Operation Hour	or Gamut 45%			72%
	Panel Orientation		Portrait (Pivot)	Landscano	/ Portrait (Pivot)
Special	IP5X Rating		PS	Lanuscape	Yes
Special Certifications	Non-Glare Panel		0		Yes
Sound	Speaker Type		eaker (5W)		Speaker (5W)
Connectivity	Video		1.4 (1)	HD	MI 1.4 (1)
	Input HDCP	HDC USB 2	P2.2	H	DCP 2.2 B 2.0 x 1
	USB		Z.O.X.T Mini Jack	US Stere	Mini Jack
	Output Audio Touch Out	N/A	Yes.1	NA Stere	Yes.1
	Wi-Fi	Y	es	1000 Table	Yes
	External Control	RS232C (In) thru	Stereo Jack, RJ45 V~ (+/- 10 %), 50/60 Hz	RS232C (In) th	u Stereo Jack, RJ45
Power	Type /Power Supply Max / Typical (W / H)	Adapter / AC 100 - 240	/13	R\$232C (In) thru Stereo Jack, RJ45 Internal / AC 100 - 240 V~ (+/- 10 %), 50/60 Hz	
	Power Rating (W / H)			30.3 / 23	35.37.28
	Consumption BTU (Max)		5.8		131.3
	Sleep Mode	0.9			0.5W
Mechanical Specifications	Set Dimensions	12.7" x 7.6" x 1.1"	12.7" x 7.6" x 1.2"	21.6" x 13.2" x 1.3"	21.6" x 13.2" x 1.4"
	Package Dimensions Set Weight		2.4 lbs.		8.8 lbs.
	Package Weight	2.0 lbs. 3.8 lbs.	4.2 lbs .	6.6 lbs. 9.0 lbs.	11.5 lbs
	VESA Mount		00mm		x 100mm
	Protection Glass Stand Type	N/A Bar Type Simple Stand (In box)		N/A	2.0T
	Bezel Width (Top/Sides/Bottom)	0.5"		0.7" (Top, Bottom), 0.4" (Sides) 32° F ~104° F	
Environmental	Operating Temperature	32°F ~104° F			
Environmental Conditions	Humidity	10 ~ 80%		10~80%	
Special Features	Key	Small Signage Display , Slim and Light Signage with Built-in MagicInfo S6, SSSP 6.0		Small Signage Display , Slim and Light Signage with Built-in MagicInfo S6, SSSP 6.0	
	Special Hardware	Temperature Sensor, Pivot Display, Clock Battery (168 Hrs Clock Keeping), Built in Speaker (5W1ch), IP5x Rating, Wi-Fi	Temperature Sensor, Pivot Display, Clock Battery (168 Hrs. Clock Keeping), Built in Speaker (5W1ch), IP5x Rating, Wi-Fi, 10 Point Touch (Max)	Temperature Sensor, Pivot Display, Clock Battery (168 Hrs. Clock Keeping), Built in Speaker (5W1ch), IP5x Rating, Wi-Fi	Temperature Sensor, Pivot Display, Clock Battery (168 Hrs. Clock Keeping), Built in Speaker (5W1ch), IP5x Rating, Wi-Fi, 10 Point Touch (Max)
	Software	Auto Source Switching and Recovery, LFD Home UI, Button Lock, Hot Key Option, Plug and Play (Initial Setting)		Auto Source Switching and Recovery, LFD Home UI, Button Lock, Hot Key Option, Plug and Play (Initial Setting)	
Internal Media Player	Processor	Cortex A721.7GHz Quad-Core CPU L1 Instruction Cache: 48KB, L1 Data Cache: 32KB, L2 Cache: 2MB		Cortex A72 1.7GHz Quad-Core CPU L1 Instruction Cache: 48KB, L1 Data Cache: 32KB, L2 Cache: 2MB	
	On-Chip Cache Memory Clock Speed	L1 Instruction Cache: 48KB, L1 Data Cache: 32KB, L2 Cache: 2MB		LT Instruction Cache: 48KB, LT Data Cache: 32KB, L2 Cache: 2MB	
	Main Memory Interface	1.7GHz 2.5GB LPDDR41.5GHz 64bit		1.7GHz 2.5GB LPDDR41.5GHz 64bit	
		Graphic Resolution: 1920 x 1080		Graphic Resolution: 1920 x 1080 Output Resolution: 3840 x 2160 (Scale up from graphic processing) 8GB (3.88GB Occupied by O/S, 4.12GB Available)	
	Graphics	Graphic Resolution: 1920 x 1080 Output Resolution: 3840 x 2160 (Scale up from graphic processing) 8GB (3.88GB Occupied by O/S, 4.17GB Available)		Output Resolution: 3840 x 2160 (Scale up from graphic processing)	
	Storage (FDM)	8GB (3.88GB Occupied by O/S, 4.12GB Available)			
	Multimedia	Video Decoder: MPEG-1/2/4, H.263, H.264/AVC, UHD H.264/AVC, VC-1, HEVC, JPEG, PNG, VP8, VP9 Audio Decoder: AC3 (DD), MPEG		Video Decoder: MPEG-1/2/4, H.263, H.264/AVC, UHD H.264/AVC, VC-1, HEVC, JPEG, PNG, VP8, VP9 Audio Decoder: AC3 (DD), MPEG	
	IO Ports Operating System	USB 2.0		USB 2.0	
	SSSP / MagicINFO	grating System         Tizen 4.0 (VDLinux)           SP / MagicINFO         SSSP 6.0 / MagicINFO S6		Tizen 4.0 (VDLinux) SSSP 6.0 / MagicINFO S6	
Safety and	Safety	60950-1		555 60950-1	
Safety and Environmental Certifications	EMC	Class B		Class B	
Certifications	Environment	ENERGY STAR 8.0, Epeat		ENERGY STAR 8.0, Epeat	
Accessories	Included	Quick Setup Guide, Warranty Card, Power Cord, Remote Controller, Batteries, Bar Type Simple Stand		Quick Setup Guide, Warranty Card, Power Cord, Remote Controller, Batteries	
Service	Warranty	7.7 (5.1.1)	.abor/ Backlight)	3 Years (Parts / Labor / Backlight)	

## Connectivity

1. RS232C In

3. HDMI

- 2. Touch Out
- 4. RJ45 5. USB
- 6. IR
  - 7. Speaker (5V1.0A)





