

# Procure



**Powered By Choice,  
Driven By You.**

# VPL-FHZ55

4,000 lumens WUXGA 3LCD Laser projector



## Overview

**See things in a new light with the world's first 3LCD laser projector** The VPL-FHZ55 is the world's first 3LCD laser projector, delivering game-changing performance and reliability in mission-critical installation applications.

It's ideal for a wide range of installation needs, producing bright, detail-packed WUXGA images with a resolution that's higher than Full HD. So your audience only sees big, beautiful pictures, not pixels.

The environmentally-friendly laser light source is teamed with 3LCD BrightEra™ technology by Sony. You'll see the difference with superb image quality and 4000 lumen brightness, plus exceptional contrast and consistent colour stability.

What's more, the laser light source typically is rated for a typical 20,000 hours operating life – far longer than the lamp in traditional projectors. Dramatically reduced maintenance requirements are complemented by a range of energy-saving features, significantly driving down total lifetime ownership costs.

The VPL-FHZ55 fits smoothly into almost any environment – from academic institutions, corporate, medical and public sector organisations to visitor attractions and retail spaces. Seamlessly blend images from multiple projectors to create super-sized displays, or even project true, accurate images onto curved surfaces. Install the projector at any angle – even on its side or upside down. With the VPL-FHZ55, there are no limits to your creative freedom.



## Features

- **First laser light projector with Sony 3LCD BrightEra™ Panel Technology**

In a world first, Sony combines a highly efficient laser light source with 3LCD BrightEra™ technology. This unique combination delivers exceptionally bright, high contrast pictures with excellent colour accuracy and stability, plus high efficiency and significantly greater durability for reduced lifetime ownership costs.

- **Up to 20,000 hours operation with virtually no maintenance**

The advanced laser light source offers a typical 20,000 hours operation without maintenance or replacement, reducing lifetime running costs compared with traditional projectors. Synchronised (20,000 hours) filter replacement cycles keep the projector in peak operating condition while reducing maintenance trips even further.

- **Clear, bright, punchy presentations in any lighting conditions**

Add more detail, impact and realism to presentations with high 4000 lumen brightness. Get your message across clearly, even when ambient light levels are high.

- **Crisp, detail-packed WUXGA resolution images**

See the finest detail in PC presentations, videos or multimedia signage with WUXGA (1920 x 1200) 16:10 resolution.

- **Up to 8,000:1 contrast ratio**

Bring new levels of impact and excitement to any presentation. Sparkling highlights are brighter and whiter, complemented by incredibly deep, rich blacks and lowlights.

- **Wide Lens Shift, Zoom and Throw Ratio**

Generous zoom, throw and lens shift adjustments give more flexibility for positioning the projector where you need it: close to ceilings, near the screen or even horizontally offset. Extend throw ratio even further with a choice of optional lenses.

- **360° free-angle installation capability**

Enjoy supreme installation flexibility: position the projector freely at any angle – or its side or even upside down.

- **Create super-size displays with Edge Blending**

Seamlessly join accurately colour-matched images from multiple projectors, simplifying creation of stunning super-size displays for retail, corporate and live event applications.

- **Project onto non-flat surfaces with Image Warping**

Easily correct image geometry for natural-looking projections – even on convex or concave surfaces. Corner and edge correction can be easily adjusted with the supplied remote and on-screen menu.

- **Project Side by Side**

Project images from two inputs at the same time: ideal for applications like video conferencing and medical training where two images need to be seen simultaneously.

- **DICOM GSDF Simulation mode**

Get a clear view of digital medical images for training and other non-diagnostic applications. NB: Conforms to GSDF (Grayscale Standard Display Function) medical standards for DICOM (Digital Imaging and Communications in Medicine).

- **Save energy at the touch of a button**

Just push the ECO MODE button on the projector or remote commander to instantly access a range of energy-saving settings.

- **Auto Dimming**

Projector brightness is gradually reduced automatically if there's no input signal, or after a pre-set time – cutting power consumption and saving energy bills.

- **Auto Brightness**

Laser output power adjusts automatically depending on picture content, saving energy when dark scenes are being projected.

- **Power Saving Picture Mute**

Touch a button on the projector remote and the picture's muted instantly, reducing power consumption by 95%. Another touch and the projector's instantly powered back up to resume your presentation.

## Technical Specifications

|  |   |  |
|--|---|--|
| Display system                               |   |  |
| ● Display system                             | 3 LCD system  |  |
| Display device                               |   |  |
| ● Size of effective display area             | 0.76"(19.3 mm) x 3 BrightEra LCD Panel, Aspect ratio: 16:10 |  |
| ● Number of pixels                           | 6,912,000 (1920 x 1200 x 3) pixels                          |  |
| Projection lens*1                            |   |  |
| ● Focus                                      | Manual  |  |
| ● Zoom - Powered/Manual                      | Manual  |  |
| ● Zoom - Ratio                               | Approx. x 1.6   |  |
| ● Throw ratio                                | 1.39:1 to 2.23:1  |  |
| ● Lens shift - Powered/Manual                | Manual  |  |
| ● Lens shift - Range Vertical                | +60%  |  |
| ● Lens shift - Range Horizontal              | +/- 32%   |  |
| Light source                                 |   |  |
| ● Type                                       | Laser diode   |  |
| Filter cleaning / replacement cycle (Max.)*2 |   |  |
| ● Filter cleaning / replacement cycle (Max.) | 20000 H (cleaning)  |  |
| Screen size*1                                |   |  |
| ● Screen size                                | 40" to 600" (1.02 m to 15.24 m) (measured diagonally)       |  |
| Light output                                 |   |  |
| ● Lamp mode: High                            | 4000 lm   |  |
| ● Lamp mode: Standard                        | 3000 lm   |  |
| Color light output                           |   |  |
| ● Lamp mode: High                            | 4000 lm   |  |
| ● Lamp mode: Standard                        | 3000 lm   |  |
| Contrast ratio (full white / full black)*3   |   |  |
| ● Contrast ratio (full white / full black)*3 | 8000:1  |  |
| Displayable scanning frequency               |   |  |
| ● Horizontal                                 | 14 kHz to 93 kHz  |  |
| ● Vertical                                   | 47 Hz to 93 Hz  |  |
| Display resolution                           |   |  |
| ● Computer signal input                      | Maximum display resolution: 1920 x 1200 dots *4             |  |

|                      |  |
|----------------------|--|
| ● Video signal input | NTSC, PAL, SECAM, 480/60i, 576/50i, 480/60p, 576/50p, 720/60p, 720/50p, 1080/60i, 1080/50i, 1080/60p, 1080/50p, 1080/24p |
|----------------------|--|

| Color system   |   |
|----------------|---|
| ● Color system | NTSC3.58, PAL, SECAM, NTSC4.43, PAL-M, PAL-N, PAL60 |

| Keystone correction (Max.) |                |
|----------------------------|----------------|
| ● Vertical                 | +/- 30 degrees |
| ● Horizontal               | +/- 30 degrees |

| OSD language   |  |
|----------------|--|
| ● OSD language | 24-languages (English, Dutch, French, Italian, German, Spanish, Portuguese, Turkish, Polish, Russian, Swedish, Norwegian, Japanese, Simplified Chinese, Traditional Chinese, Korean, Thai, Vietnamese, Arabic, Farsi, Finnish, Indonesian, Hungarian, Greek) |

| INPUT OUTPUT (Computer/Video/Control) |  |
|---------------------------------------|--|
| ● INPUT A                             | RGB / YPbPr input connector: 5BNC (female)<br>Audio input connector: Stereo mini jack  |
| ● INPUT B                             | RGB input connector: Mini D-sub 15-pin (female)<br>Audio input connector: Stereo mini jack (shared with INPUT C)                 |
| ● INPUT C                             | DVI-D input connector: DVI-D 24-pin (Single link), HDCP support<br>Audio input connector: Stereo mini jack (shared with INPUT B) |
| ● INPUT D                             | HDMI input connector: HDMI 19-pin, HDCP support  |
| ● S VIDEO IN                          | S video input connector: Mini DIN 4-pin<br>Audio input connector: Pin jack (x2) (shared with VIDEO IN)                           |
| ● VIDEO IN                            | Video input connector: Pin jack<br>Audio input connector: Pin jack (x2) (shared with S VIDEO IN)                                 |
| ● OUTPUT                              | Monitor output connector*5: Mini D-sub 15-pin (female)<br>Audio output connector*6: Stereo mini jack (variable out)              |
| ● REMOTE                              | RS-232C connector: D-sub 9-pin (female)  |
| ● LAN                                 | RJ-45, 10BASE-T/100BASE-TX   |
| ● IR (Control S)                      | Control S input connector: Stereo mini jack  |

| Acoustic noise        |       |
|-----------------------|-------|
| ● Lamp mode: Standard | 35 dB |

| Operating temperature / Operating humidity   |  |
|--|--|
| ● Operating temperature / Operating humidity | 0 °C to 40 °C (32 °F to 104 °F) / 35% to 85% (no condensation) |

| Storage temperature / Storage humidity   |  |
|--|--|
| ● Storage temperature / Storage humidity | -20 °C to +60 °C (-4 °F to +140 °F) / 10% to 90% (no condensation) |

| Power requirements   |   |
|----------------------|---|
| ● Power requirements | AC 100 V to 240 V, 4.6 A to 1.9 A, 50/60 Hz |

| Power consumption   |                        |
|---------------------|------------------------|
| ● AC 100 V to 120 V | Lamp mode: High: 449 W |
| ● AC 100 V to 120 V | Lamp mode: High: 426 W |

| Power Consumption (Standby Mode) |   |
|----------------------------------|---|
| ● AC 100 V to 120 V              | 0.2 W (when "Standby mode" is set to "Low") |
| ● AC 220 V to 240 V              | 0.3 W (when "Standby mode" is set to "Low") |



| Power Consumption (Networked Standby Mode)        |   |
|---|---|
| ● AC 100 V to 120 V                               | 8.5 W (LAN) (when "Standby Mode" is set to "Standard")  |
| ● AC 220 V to 240 V                               | 9.5 W (LAN) (when "Standby Mode" is set to "Standard")  |
| Standby Mode / Networked Standby Mode Activated   |   |
| ● Standby Mode / Networked Standby Mode Activated | After about 10 Minutes  |
| Heat dissipation                                  |   |
| ● AC 100 V to 120 V                               | 1528 BTU/h  |
| ● AC 220 V to 240 V                               | 1450 BTU/h  |
| Dimensions (W x H x D)                            |   |
| ● Dimensions (W x H x D) (without protrusions)    | Approx. 390 x 134 x 487 mm (15 11/32 x 5 9/32 x 19 3/16 inches)   |
| Mass  |   |
| ● Mass  | Approx. 11 kg (25 lb)   |
| Supplied accessories                              |   |
| ● Remote commander                                | RM-PJ19   |
| Optional accessories                              |   |
| ● Projection lenses                               | VPLL-Z2009/Z1024/Z1032  |
| ● Projection lens adapter                         | PK-F30LA1   |
| Notes   |   |
| ● *1  | With supplied standard lens   |
| ● *2  | This figure is expected maintenance time, not guaranteed time. The actual value depends on the environment and how the projector is used. |
| ● *3  | The value is average.   |
| ● *4  | Available for VESA Reduced Blanking signal.   |
| ● *5  | From INPUT A and INPUT B.   |
| ● *6  | Works as an audio switcher function. Output from a selected channel; not available in standby.  |

## Lenses



**VPLL-1008**  
Projection Lens for the VPL-F Series



**VPLL-2007**  
Projection Lens for the VPL-F Series



**VPLL-Z1024**  
Projection Lens for the VPL-F Series



**VPLL-Z1032**  
Projection Lens for the VPL-F Series



**VPLL-Z2009**  
Projection Lens for the VPL-F Series