

Procure



**Powered By Choice,
Driven By You.**

Display System

Display System

3LCD system

Display Device

Size of Effective Display Area

0.64" (16.3 mm)x 3 BrightEra LCD Panel, Aspect ratio: 16:10

Number of Pixels

6,912,000 (1920 x 1200 x 3) pixels

Projection Lens

Focus

Manual

Zoom

Manual (Approx. x 1.6)

Lens shift

Manual, Vertical -35% to +55%, Horizontal: +/-15%

Throw Ratio

1.23 : 1 to 1.97 : 1

Light Source

Light Source

Laser diode

Screen Size

Screen Size

40" to 300" (1.02 m to 7.62 m) (measured diagonally)

Light Output *1

Mode: Standard

6,000lm *2

Mode: Standard (Center)

6,500lm *3

Mode: Middle

4,500lm

Color Light Output*1**Mode: Standard**

6,000lm

Mode: Middle

4,500lm

Contrast Ratio (full white / full black) *1**Contrast Ratio (full white / full black) *1**

∞ :1

Displayable Scanning Frequency**Horizontal**

15 kHz to 92 kHz

Vertical

24 Hz to 92 Hz

Keystone Correction (Max.)**Keystone Correction (Max.)**

Horizontal: +/-30 degrees

Vertical: +/-30 degrees

Accepted Signal Resolution**Computer Signal Input**

Maximum signal resolution: 1920 x 1200

(4K/30p, 3840 x 2160 acceptable)

Video Signal Input

NTSC, PAL, SECAM, 480/60i, 576/50i, 480/60p, 576/50p, 720/60p, 720/50p, 1080/60i, 1080/50i, 1080/60p, 1080/50p 4k/30p, 4k/25p, 4k/24p (4k means 3840)

INPUT / OUTPUT

INPUT A

RGB / Y PB PR input connector: Mini D-sub 15 pin (female)
Audio input connector: Stereo mini jack

INPUT B

HDMI input connector: HDMI 19-pin, Digital RGB/Y PB PR, HDCP support
Audio input connector: HDMI audio support

INPUT C

HDMI input connector: HDMI 19-pin, Digital RGB/Y PB PR, HDCP support
Audio input connector: HDMI audio support

INPUT D

HDBaseT interface connector: RJ45, 4 play (Video, Audio, LAN(100BASE-TX), RS-232C)

VIDEO IN

Video input connector: Phono jack (Composite)

OUTPUT

Audio output connector: Stereo mini jack

REMOTE

D-sub 9-pin (male) / RS232C

LAN

RJ45, 10BASE-T / 100BASE-TX

USB

TYPE-A x 1 (for F/W update), TYPEA for Power supply

Speaker

Speaker

16 W

OSD Languages

OSD Languages

27-language (English, French, German, Italian, Spanish, Portuguese, Japanese, Chinese, Korean, Russian, Dutch, Norwegian, Swedish, Thai, Arabic, Turkish, Polish, Vietnamese, Farsi, Finnish, Indonesian, Hungary, Gleeck, Czech, Slovakia, Romania)