MAXHUB

# MAXHUB UC S07





Ultra-Wide Angle, All-in-One Video Soundbar for Huddle & Small Rooms

MAXHUB UC S07 is an all-in-one videobar with a high-resolution camera, a studio-quality speaker, and a microphone range that can cover extra-large spaces. A unified communication solution supports connecting with a laptop. The videobar can be used as a wide-angle camera, treble & bass speaker, and noise reduction microphone with smart features such as Auto Frame, Speaker Tracking, and Echo Cancellation.






#### Ultra HD 4K

Silky smooth UHD video of up to 30fps



# 120° FOV

Provides full-room coverage



## **Auto Framing**

Al Vision Intelligent face detection




# Voice Localization

Speaker Tracking Voice tracking




#### Tweeter + Woofer

HI-FI quality speaker for an exceptional audio experience



#### PoE

PoE support to simplify installation and minimize cost



### **USB Plug & Play**

Single cable BYOD, auto-detect video, audio & HDMI



#### PIR Sensor

Auto on/off Completely hands-free and energy saving

Camera			
Pixel	12M		
Sensor	1/2.3-inch 12MP Sony sensor		
Resolution and Frame Rat	e		
H.264/MJPEG	(1) 3840 x 2160 (4) 1280 x 720 (7) 800 x 600 (10) 480 x 270	(2) 2560 x 1440 (5) 1024 x 576 (8) 640 x 480 (11) 352 x 288	(3) 1920 x 1080 (6) 960 x 540 (9) 640 x 360 (12) 320 x 240
YUY2	(1) 640 x 480 (4) 352 x 288 (7) 160 x 120	(2) 640 x 360 (5) 320 x 240	(3) 480 x 270 (6) 320 x 180
ZOOM		5x Digital Zoom	
Output Format	MJPG; YUY2; H.264		
Field Of View	120° (D)		
Adjustable Angle	± 15° (V)		
Focus Mode	Fixed-Focus		
Focus Distance		1m	
Special Features Sp	Auto Framing: automatic adjustment FOV to fit in all participants Speaker Tracking: voice triggered people tracking 10 Zooming Pre-sets for instant setting up		

Audio	
Speaker	
Sound Chanel	1.1
Output Power	8W + 3W
Maximum Sound Pressure	80dBSPL@1m
Signal to Noise Ratio	>75dB
Frequency Range	150Hz ~ 18kHz
Microphone	
Microphone Quantity	6
Voice Pickup Range	8m
Microphone Frequency Range	100Hz ~ 7.5kHz
Special Features	Noise Reduction, Echo Cancellation, Anti-Reverberation, Built-in AGC Algorithm
Input/Output Port	
USB 3.0 Type-C	Connect USB host, upgrade system, etc.
Audio Out	Used for external audio equipment
DC 2.0	Used for 12V power input power supply
RJ45	No IP Support, only provides PoE power

Power	
Power Requirements	12V
Overall Power(Max.)	10W
PoE Power	Yes (IEEE 802.3af or 802.3at)

#### Compatibility

Support major VC software including ZOOM, Microsoft® Teams, Google Meet, Google Hangouts, Cisco WebEx®, RingCentral, etc.

System Requirements

Supports Windows XP/7/8.1/10/11, Android 8.1 or higher, and MAC OS 10.12 or higher

**Application Supported** 

MAXHUB Align software for Windows & Mac OS

PIR Sensor

In power-on mode, it will automatically enter standby state If no moving object is detected within 3 meters within 30 minutes, minimizing energy consumption; In standby mode, it automatically starts up when detecting moving objects within 3 meters, simplifying the setup process.

Mount

Wall-mounted
TV mount kit (Optional)

462 x 76 x 93 mm (18.2 x 3.0 x 3.7 inch)
1pcs 538 x 160 x 169 mm (21.2 x 6.3 x 6.7 inch) 4pcs 628 x 433 x 380 mm (24.7 x 17.0 x 15.0 inch)
1.05Kg/2.31lbs
1pcs 2.55kg/5.62lbs 4pcs 12.00kg/26.46lbs

<b>Environmental Condition</b>	
Operation Temperature	0°C - 40°C
Operation Humidity	10% - 90%RH
Storage Temperature	-20°C - 60°C
Storage Humidity	10% - 90%RH
Altitude	Below 5000 meters

Warranty 3 year hot swap Accessories one year

#### What's In The Box

included

1 x USB Cable (1.8m/70.9 inch), 1 x Remote Control
1 x Power Adapter, 1 x Wall-mounted Components, 1 x Peeping Cover

