

Procure



**Powered By Choice,
Driven By You.**

VIEWBOARD

CDE5561T

Key Features



Product Description

The ViewSonic® CDE5561T 65" (54.6" viewable) Full HD interactive flat panel display is a perfect solution for interactive business and educational classroom applications. This 20-point touch-enabled display, paired with PC-less operation with pre-installed annotation software, allows multiple users to simultaneously write or draw on the display's 7H hardness surface using fingers or styluses. 350-nit brightness and wide viewing angles provide better visual performance in well-lit rooms, and its flicker-free and blue light filter eye-care technologies create a comfortable viewing environment. With a built-in dual core processor and 8GB internal storage, as well as integrated versatile connectivity including HDMI, VGA, YPbPr, RS232, RJ45 and USB ports, this display provides powerful computing for annotation and multimedia playback without the need for a PC. This Energy Star certified display delivers optional slot-in PC (NMP711-P10/ NMP710-P8) capability, offering Windows® 10 OS and ViewBoard 2.1 annotation software, for more computing-intensive interactive applications. The CDE5561T features a VESA-compatible design and can be placed on a wall mount, or on an optional trolley cart for flexible installation in classrooms and corporate meeting rooms.

Visit Us www.viewsonic.com

LCD PANEL		OPERATING CONDITIONS	
Panel Size:	54.6"	Temperature:	0°C to 40°C
Type/Tech:	TFT LCD Module with LED Backlight	Humidity:	20% ~ 80% non-condensing
Display Area:	1209.6(H) x 680.4(V) (54.6" diagonal)	DIMENSIONS (W X H X D)	
Aspect Ratio:	16:9	Physical (inch / mm):	51.34x31.5x3.82 / 1304x800x97
Resolution:	1920 x 1080	WEIGHT	
Colors:	16.7 M	Net (lb / kg):	71.65 / 32.5
Brightness:	350 nits (typ.)	REGULATIONS	
Contrast Ratio:	1200:1 Typ.	FCC, cTUVus, CB, CE, RCM	
Response Time:	8ms	PACKAGE CONTENTS	
Viewing Angles:	H = 178, V = 178 typ.	VGA cable / Power cable x 4 / Remote control / USB cable / Audio cable / Touching pen x 3 (LB-PEN-003) / User manual CD wizard / RS232 adapter	
Backlight Life:	30,000 Hours Typ.		
Surface Treatment:	AG coating (7H)		
Orientation:	Landscape		
TOUCH			
Type/Tech:	IR Recognition		
Touch Resolution:	32767 x 32767		
Touch Point:	20 point for gesture, 10 point for writing		
INPUT			
HDMI:	x3		
RGB / VGA:	x3		
Audio:	x3 PC audio(3.5 mm)		
CVBS:	x1		
RS232:	x1		
OPS:	PC Slot (proprietary)		
OUTPUT			
RGB / VGA:	x1		
Audio:	x1 Earphone Out		
SPDIF:	x1		
LAN			
RJ45:	x1		
USB			
Type A:	x3 (USB 2.0 including 2 USB ports in front), x1 (USB 3.0)		
Type B:	x1 (for touch)		
SPEAKERS			
10Wx2			
COMPATIBILITY			
RGB PC/HDMI PC:	up to 1920x1080@60Hz / 1080p		
CVBS:	480i		
HDMI:	480i, 480p, 720p, up to 1080p		
BUNDLE SOFTWARE			
ViewBoard Lite, ViewBoard 2.1			
POWER			
Voltage:	100-240VAC +/- 10% 50/60Hz Wide Range		
Consumption:	162W (Typ.) < 0.5 W ("Off")		
ERGONOMICS			
Wall Mount:	400 x 400		