



CDE92UW -92-INCH ULTRA-WIDE DISPLAY, 21:9 ASPECT RATIO, 5120 X 2160 RESOLUTION, 500 CD/M2 HIGH BRIGHTNESS, 24/7 OPERATION RATING, HDMI, DP, USB-C, RJ45, BUILT-IN CONTENT SHARING, REMOTE MANAGEMENT, AV CONTROL SYSTEM INTEROPERABILITY, LANDSCAPE AND PORTRAIT


Key Features



92
DISPLAY



IPS-Type
PANEL



RESOLUTION



Product Description


The ViewSonic® CDE92UW is a 92" ultrawide 5K display that is optimized for Microsoft Teams Rooms and ideal for inclusive meetings and presentations. Featuring a 21:9 aspect ratio, this ultrawide display offers 33% more screen real estate than a traditional 16:9 aspect ratio - delivering more than enough space for collaboration and more inclusive meetings. With 24/7 reliability, 500-nit high brightness and a 25% high haze anti-glare screen, this versatile display can also function as an immersive digital signage solution. Versatile connectivity options include HDMI, DisplayPort and USB-C with 100W power delivery. Plus, an all-in-one design features an integrated octa-core SoC on Android 13 to ensure seamless operation without external devices.

Specifications

More Information	
UPC	766907027969
Screen Size	92
Viewable Area (in.)	91.52
Display Resolution	5120 x 2160
Light Source	DLED
Orientation	Landscape / Portrait
Static Contrast Ratio	5,000:1
Dynamic Contrast Ratio	5,000:1
Brightness	500 cd/m2
Colors	1.07B
Viewing Angles	178º horizontal, 178º vertical
Backlight Life (Hours)	50,000
Response Time (Typical GTG)	6.5ms
Panel Surface	Anti-Glare type, Hard-coating (3H), Haze 25%
Panel Type	IPS-Type
Aspect Ratio	21:9
Operation Rating	24/7
Internal Speakers	20W x 2 (Speakers) + 20W x1 (Subwoofer)
3.5mm Audio In	1
3.5mm Audio Out	1
SPDIF Audio Out	1
HDMI Out	1
DisplayPort	1
Ethernet LAN (RJ45)	2
HDMI 2.1 In	1
HDMI 2.0 In	3
RS232 In	1
USB 2.0 Type A	1
USB 3.0 Type A	4
USB Type C	1
OPS PC Slot	1
Media Player Type	Media Player
CPU	Rockchip RK3588 (A76 x 4, A55 x 4)

GPU	Quad-core MALI-G610
Operating System	Android™ 13.0
RAM	8GB
Memory Type	LPDDR
Storage Capacity	128GB
Storage Type	eMMC
Voltage	100-240 VAC +/- 10% Wide Range, 50-60Hz +/-3 Hz
Stand-by	<0.5W
Temperature	32-104° F (0 - 40° C)
Humidity (non-condensing)	20-80%
VESA Compatible	800 x 600 mm
Screw Size	M8
Screw Length (mm)	25
Gross (lbs)	138.01
Net (lbs)	95.68
Gross (kg)	62.6
Net (kg)	43.4
Packaging (in.)	92.52 x 44.72 x 8.5
Physical (in.)	85.91 x 37.16 x 3.35
Packaging (mm)	2350 x 1136 x 216
Physical (mm)	2182 x 943.8 x 85.2
Regulations	cTUVus, FCC, Energy Star 8.0, RoHS, Mexico NOM, Mexico Energy
Package Contents	CDE92UW Ultra-wide Display, 3m power cable, USB Type C cable 1.8m(USB-IF certified), Remote control, Remote control AAA Battery x 2, Quick Start Guide, RS232 adapter, Clamp x 5, Camera Plate x 2 (1 for VB-CAM-201, 1 for UMB202), Screw x 8 (camera 2+2, wal
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.
Warranty	Three-year limited warranty on parts, labor and backlight

UPC: 766907027969



Contact Sales

[ViewSonic.com](https://www.viewsonic.com)

888.881.8781

email:

salesinfo@viewsonic.com