Procure



Powered By Choice, Driven By You.

Key **Features**

Integrated 10-point Multi-touch | Built-in Quad Core CPU Media Player with 16GB Storage | Embedded LAN, Wi-Fi, and Internet Browser | Internal Scheduler | Content Management Software



Product **Description**

Content deployment, interactivity, and messaging couldn't be easier than with the ViewSonic* CDM4300T. Featuring a 10-point touchscreen and internal media player, this Full HD 1080p display gives you everything you need for easy interactive digital signage – right out of the box. Loaded with a powerful, high-performance quad core CPU and 16GB of storage (upgradeable to 32GB), the integrated $media\ player\ ensures\ continuous\ hours\ of\ smooth,\ high-definition\ multimedia\ content\ delivery. For\ expanded\ connectivity,\ the\ media\ player\ also\ features\ built-in\ LAN\ /\ Wi-Fi.\ Additional\ professional-index of\ player\ professional-index of\ player\ professional-index of\ player\ player\ professional-index of\ player\ player\$ grade features include, landscape and portrait orientation, an internal scheduler, tiling capability for video wall applications, and a durably designed cabinet for reliable 24/7 operation. For more detailed information on how ViewSonic ViewBoards can best be utilized in a school environment, see our <u>ViewBoard FAQs</u>.









450 cd/m2 BRIGHTNESS

24/7

call: 888 881 8781 **Contact Sales** email: salesinfo@viewsonic.com visit: viewsonic.com

Display:

Display Size (in.): 43
Viewable Area (in.): 42.51

Orientation: Landscape / Portrait

Light Source:ELEDResolution:1920 x 1080Aspect Ratio:16:9Static Contrast Ratio:1,100:1Backlight Life (Hours):50,000Brightness:450 cd/m2Response Time (Typical GTG):12ms

Viewing Angles: 178° horizontal, 178° vertical
Panel Surface: Anti-glare, Hard coating (3H)

Operation Rating: 24/7

Embedded Player:

CPU: Quad core A9 CPU - RK3188
Interface: OSD / Remote Control

Audio:

Internal Speakers: 10W (x2)

Connector:

HDMI 1.4(2), DVI-I(1), DVI-I Out(1), Display Port(1), Display Port Out(1), 3.5mm Audio In(1), 3.5mm Audio Out(1), Speaker Out(2), USB 2.0(2), USB 2.0 Type B(1), Micro USB(1), RS232(1), RS232 Out(1), Ethernet LAN (RJ45)(1), Micro SD Card Slot(1), IR in(1), IR out(1)

Power:

Voltage: 100-240 VAC, 50-60Hz

Consumption (max): 110W
Consumption (typical): 60W
Stand-by: <.5W

Controls:

On Screen Display: Input, Volume, Backlight, Audio, Screen, Display, Adjust
Remote Control: Volume, Channel, Source, Mute, Back, Input, Menu

Operating Conditions:

Temperature: 32–95° F (0 - 35° C)

Humidity (non-condensing): 20-80%

Weight (metric):

 Net (kg):
 23.5

 Net Without Stand (kg):
 19.4

 Gross (kg):
 24.6

Weight (imperial):

 Net (lbs):
 51.8

 Net Without Stand (lbs):
 42.8

 Gross (lbs):
 54.2

Dimensions (metric) (WxHxD):

 Packaging (mm):
 1219 x 811 x 223

 Physical (mm):
 1002.6 x 725 x 400

 Physical Without Stand (mm):
 1002.6 x 590.8 x 64

Dimensions (imperial) (WxHxD):

 Packaging (in.):
 48.0 x 31.9 x 8.8

 Physical (in.):
 39.5 x 28.5 x 15.8

 Physical Without Stand (in.):
 39.5 x 23.3 x 2.5

Mount:

VESA Compatible: 400 x 400 mm

General:

Warranty: Three-year limited warranty on parts, labor and backlight

Recycle/Disposal: Please dispose of in accordance with local, state or federal laws.

PACKAGE CONTENTS: CDM4300T, Remote control, CD User Manual, Quick Start Guide, power cables, DVI to VGA cable, RS232 cable, IR sensor cable, RS232 daisy chain cable, USB cable (Type A-B)

Regulations: UL/cUL, FCC, Energy Star 7.0, UL-MX-CoC, Mexico Energy

UPC: 766907935516

Accessories:

, CD-EE-24-42, CD-EW-42-01, CD-EW-42-02, NMP-012, NMP520-W, NMP620-P10, NMP620-P10X, STND-044, SW-071, SW-071-2, SW-072, SW-072-2, SW-073, SW-073-2, SW-074, SW-074-2, SW-075-2, SW-090, SW-091, SW-092, SW-093, SW-094, SW-095, SW-096, VC10, VC10-S, VCB10, WMK-014, WMK-050, WMK-054, SW-014, SW-015

Copyright © ViewSonic Corporation 2000-2019. All rights reserved. (01/28/2019 02:30 AM PST)