


Procure



**Powered By Choice,
Driven By You.**



万胜凯机械有限公司
WIDESKY MACHINERY CO.,LTD.

模具恒温机 MOULD TEMP.CONTROLLER

产品特点 FEATURES:

温度控制表采用日本、德国、台湾产品，精确可控制在 $\pm 1^{\circ}\text{C}$ 内，省电35%以上。单组电热，可方便维护。
电热管采用不锈钢材质采用进口高级组件，使用年限长。加温及冷却时间快速，使用年限长。安全保护及故障指示系统完善。

The Temperature control meter adopts the Janpan, germany Taiwan brand. Precise in $\pm 1^{\circ}\text{C}$ and save over 35% electricity
Two sets of electric heater which can be used jointly or ndependent of each other, electric heater cylinder made from stainless steel. Use imported components, longer life. Rapid heating and cool off speeds, longer life Complete with safety protection and error Indicatoin system.

水式 WATER TYPE:

自动补水系统
压力过载自动泄压
总电源过电流无熔丝断路器
泵反转保护及指示灯
泵过载保护及指示灯
异常警报蜂鸣器
泄压回路
过热保护及指示灯
缺水保护及指示灯

Auto supply water system
Auto relif when over pressure
Main circuit breaker
Pump reverse protect and direct lamp
Pump overload protect and direct lamp
Abnormal alam buzzerBY-PASS
BY-PASS circuit
Overheat protection and direct lamp
Water stor tage protect and direct lamp

油式 OILTYPE:

自动排气系统
总电源过电流无熔丝断路器
泵反转保护及指示灯
泵过载保护及指示灯
异常警报蜂鸣器
泄压回路
过热保护及指示灯
缺油保护及指示灯

Auto drain air system
Main circuit breaker
Pump reverse protect and direct lamp
Pump overload protect and direct lamp
Abnormal alam buzzerBY-PASS
BY-PASS circuit
Overheat protection and direct lamp
Oil storage protect and direct lamp



技术参数SPECIFICATIONS

规格 Specification	运水式Water Type			运油式Oil Type				
Model 型号	FST-6-W	FST-9-W	FST-12-W	FST-6-O	FST-9-O	FST-12-O	FST-6H-O	FST-12H-O
Control Range 温控范围	Normal Temp. 常温-90℃			Normal Temp. 常温-160℃			Normal Temp. 常温-200℃	
Voltage 电压	220V-460V 3PHASE 50HZ/60HZ			220V-460V 3PHASE 50HZ/60HZ				
Cooling Method 冷却方式	直接冷却 Direct Cooling			间接冷却 Indirect Cooling				
Fluid 传热媒体	水 Clean Water			传热油 Heat Transfer Oil				
Heating 加热能量	6	9	12	6	9	12	6	12
Pump Power 泵马力	0.375	0.375	0.75	0.375	0.375	0.75	0.375	0.75
Pump Capacity 泵流量(KW)	80	80	110	60	60	90	60	90
Pump Pressure 泵压力(KG/CM MAX)	3.0	3.0	3.5	1.5	1.5	2.0	1.5	2.0
Cooling Water pipe 冷却水管径 (INCH)	1/2	1/2	1/2	1/2	1/2	1/2	1/2	1/2
Process Fluid pipe 热媒管径 (INCH)	1/2x4	1/2x6	1/2x8	1/2x4	1/2x6	1/2x8	1/2x4	1/2x8
Weight 重量(KG)	650*340*580	650*340*580	750*400*700	650*340*580	750*400*700	750*400*700	650*340*580	750*400*700
Dimension 外型尺寸(MM)	54	72	90	58	75	95	58	75