

Procure



**Powered By Choice,
Driven By You.**



万胜凯机械有限公司
WIDESKY MACHINERY CO.,LTD.

除湿机 PLASTIC DEHUMIDIFIER

产品特点 FEATURES:

集除湿、干燥、二段送料功能于一体，并可选购三段送料功能。转轮更换费用低，经久耐用，使用寿命长。全不锈钢双层保温式干燥料桶采用下吹风管设计，搭配旋风排气装置，防止热能散失，确保温度，提高干燥效率。该机配备微电脑控制为标准装备，可选PLC控制搭配LCD触控式人机界面，操作集中方便，可控制整机自动运行。回路密闭的送料系统，可避免干燥后的原料因接触外界空气而再度回潮。断续式空气输送清扫，可以给成型机适量供料。又可以让输送配套管内不留残余物采用无阀门空气切断方式，排除了使用阀门等控制方式易造成的卡料、异物混入等不良现象。机器占地小，移动方便，可任意更换机台使用。

Rotor type design.

PID temperature control system, display the regenerate air temperature and return air temperature. Phase protector and overload protector. Delay 3 minutes to shutoff and display the function. Over-temperature alarm and meet fault stop compact, light weight construction, looks nice. Simple component, easy tousing and maintain. Control components from OMRON, SIEMENS etc Standard accessories contain quick-coupling and TEFLON-hoses



Model 型号	WCD	25/60	50/60	50/90	75/90	100/120	100/150	150/150	200/200	300/200	400/30	500/400	600/500
Insulation Tank Capacity 保温料桶容量	KG	25	50	50	75	100	100	150	200	300	400	500	600
Dehumidifier air volume 除湿机风量	M³/H	60	60	90	90	120	150	150	200	200	300	400	500
Drying blower power 干燥风机功率	KW	0.37	0.37	0.75	0.75	1.1	1.5	1.5	2.2	2.2	3.75	5.5	7.5
Regeneration blower power 再生风机功率	KW	0.12	0.12	0.12	0.12	0.18	0.18	0.18	0.37	0.37	0.37	0.75	0.75
Dry heating power 干燥电热功率	KW	2.4	2.4	3.6	3.6	6	6	9	12	15	15	18	18
Renewable heating power 再生电热功率	KW	2.4	2.4	2.4	2.4	2.4	2.4	2.4	3.6	3.6	3.6	6	6
Feeding blower power 送料风机功率	KW	0.75	0.75	0.75	0.75	1.1	1.1	1.1	1.1	1.1	1.1	2.2	2.2
Feeder pipe 送料机配管	INCH	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	2	2
Vacuum Hopper 真空料斗	L	6	6	6	6	6	6	6	12	12	12	12	12
Electric eye hopper 电眼料斗	L	1.5	3	3	6	6	6	6	12	12	12	12	12
Weight 重量	KG	320	344	375	385	442	450	475	560	585	635	640	750