


Procure



**Powered By Choice,
Driven By You.**



万胜凯机械有限公司
WIDESKY MACHINERY CO.,LTD.

冷却水塔 ROUND COOLING TOWER

产品特点 FEATURES:

风扇：角度均为可调性轴流式，采用高级工程塑料制造。

马达：均为全封闭式，可应用于恶劣的气候环境中。

壳身和水盘：均采用玻璃钢材料制造，不会被腐蚀、无需油漆，经久耐用，降低保养成本。

散热胶片：采用耐高温硬聚氯乙烯片材制造，入水温度可达摄氏54度，胶片特殊结构。使冷却水能最大面积接触胶片及空气 阻力减至最小，热交换能量高。

The angles of all the fans are regulative and axial-flow, which are made of advanced engineering plastics.

All the motors are sealed, which can be used in the severe weather and circumstances.

The casing and water plate of the cooling tower are made of fiberglass, which will not be corroded, and no painting is needed. They can be used for a long time with very low maintenance cost.

The radiating film is made of polyvinyl chloride which is hard and heat-resisting. The temperature in the water is up to 54°C and the special structure enables the water to touch the film in the biggest area with low air resistance. The energy exchanging efficiency is very high.



技术参数SPECIFICATIONS

DATA参数	MODEL型号	RTA	10T	15T	20T	25T	30T	40T	50T	60T	80T	100T	125T	150T	175T	200T
WATER FLOW 流量	MP/H	7.81	11.7	15.62	19.51	23.40	31.21	39.24	46.8	62.64	78.12	97.56	117.00	136.80	156.24	
WIND VOLUME 风量	CMM	85	140	160	200	230	280	330	420	450	700	830	950	1150	1250	
SOUND VOLUME 噪音	DbA	47	48	50	52	54	56.5	57.5	57	59	60	60	60	60	60	
MOTOR 电机	KW	0.18	0.37	0.55	0.75	0.75	1.5	1.5	1.5	1.5	2.25	2.25	2.25	3.75	3.75	
NET WEIGHT 净重	KG	48	54	67	98	120	130	190	240	260	500	540	580	860	880	
WORKING WEIGHT 运行重	KG	190	290	300	500	530	550	975	1250	1280	1600	1640	1680	1960	1980	
TOWER HEIGHT 塔高	MM	1725	1855	1930	1985	1840	1920	2125	2380	2475	2795	2945	2945	3515	3515	
CASING 壳身	MM	1100	1000	1220	1200	1220	1250	1300	1330	1430	1460	1550	1650	1800	1900	
WIND ENTRANCE 入风口	MM	170	170	170	245	245	245	245	325	325	325	325	325	365	560	
WATER BASE 水盘	MM	320	340	340	360	360	360	400	410	410	465	465	465	465	465	
WATER LNILTER/OUTLET 出入水管	W/IWO	40/40	50/50	50/50	80/80	80/80	80/80	80/80	100/100	100/100	125/125	125/125	150/150	150/150	150/150	
FAN DIAMETER 风扇直径	MM	635	635	770	770	770	930	930	1180	1180	1450	1450	1450	1750	1750	
BASE DIAMETER 水盘直径	MM	930	1200	1200	1420	1660	1660	1900	2100	2100	2914	2914	2914	3310	3310	
OVER FLOW/DRAIN 满水/排水	OF/DR	25/25	25/25	25/25	25/25	25/25	25/25	25/25	25/25	25/25	25/25	25/25	25/25	40/40	40/40	
FLOAT /SUPPLY 浮波/补水	FV/QS	15/15	15/15	15/15	15/15	15/15	15/15	15/15	20/20	20/20	25/25	20/20	20/20	20/20	20/20	
FOUNDATION HEIGH 基础高度	MM	300	300	300	300	300	300	300	300	300	300	300	300	300	300	
FOUNDATION WIDTH 基础宽度	MM	300	300	300	300	300	300	300	300	300	300	300	300	300	300	
WATER CABINET BASE 水箱基础	MM										800	800	800	1000	1000	
CENTRAL DIAMETER 中心直径	MM	473	779	779	1000	1110	1110	1350	1540	1540	2440	2440	2900	2900	3360	
SCREW SPE. 螺丝规格	BC	M10	M10	M10	M10	M10	M12	M12	M12	M12	M12	M12	M12	M14	M14	