

DATA SHEET

APPRIMO TOUCH 10 UCX-T

TABLETOP TOUCH PANEL CONTROL



Control your video meetings with ease using a 10" floating tabletop touchscreen display designed for sharp, easy-to-read visuals from anywhere at the table.

FEATURES

- **One cable does it all** — A single cat-cable connection provides both data and power via PoE+ from Devio UCX. Plug it in and it auto pairs to Devio UCX.
- **Instant, glare-free response** — An instant-response capacitive touch layer with an optically bonded LCD reduces glare and keeps every tap responsive.
- **Stays looking pristine** — An anti-fingerprint coating keeps the display clean through daily use.
- **Modern, rigid profile** — Unique stamped metal construction delivers a thin, rigid build that looks as good as it feels.
- **Stays put on the table** — An anti-slip foot keeps the panel securely in place, no matter how often it's used.
- **Wakes as you walk in** — A proximity sensor wakes the device the moment you enter the room.
- **BYOM out of the box** — A USB-C port enables BYOM and content sharing right at the table.
- **Cable clutter, solved** — Built-in cable management keeps the tabletop clean and professional.

The Apprimo Touch 10 UCX-T is a premium 10-inch tabletop touch panel designed for Devio UCX meeting room systems, making video meeting control simple, responsive, and visually clear. Its floating display, optically bonded LCD, anti-glare and anti-fingerprint surface, and instant-response capacitive touch layer create a refined experience worthy of being a room centerpiece.

The thin, stamped-metal construction provides a rigid, modern profile, while the anti-slip foot keeps the controller securely in place on the table. A proximity sensor wakes the panel as users enter the room, and a single-cable PoE+ connection from Devio UCX simplifies both installation and power.

Built-in USB-C enables convenient BYOM and content sharing at the table, with optional power adapter support for laptop charging and integrated cable management for a clean, professional installation.

ARCHITECTS & ENGINEERS SPECIFICATIONS

The touch panel shall be a dedicated touch controller for unified communications room systems. The touch panel shall utilize the Microsoft Device Ecosystem Platform (MDEP) operating system based on Android 15. The touch panel shall provide native support for Microsoft Teams Rooms for Android Appliance. The touch panel shall be compatible with the Biamp Devio™ UCX 1000, UCX 2000, and UCX 3000 UC compute devices. The touch panel shall provide a 10.1-inch diagonal IPS LCD display with 1920 x 1200 resolution and auto-adjusting brightness up to 380 cd/m². The touch panel shall provide a capacitive touchscreen optically bonded to the LCD, with an anti-fingerprint coating and diffuse-texture finish. The touch panel shall include an ambient light sensor for automatic brightness adjustment, an ultrasonic beacon for Microsoft Teams Rooms proximity join, and a motion sensor to wake the system on motion. The touch panel shall provide one USB-C input supporting DisplayPort 1.4a Alt Mode for content sharing and BYOM (Bring Your Own Meeting) switching at up to 4K at 30 Hz. The touch panel shall provide one Ethernet port (100/1000) for primary LAN connection and shall be powered as a PoE+ Class 4 powered device, with an optional 100W USB-C power supply available for Wi-Fi deployments and 65W USB-C device charging. The touch panel shall provide Wi-Fi 6 wireless LAN. The touch panel shall support remote status monitoring via Biamp Workplace; Microsoft 365 Admin, Entra ID, and Intune management via MDEP; and Teams Admin Center and Teams Rooms Pro Management Portal for Microsoft Teams Rooms. The touch panel shall provide platform security including Secure Boot and Signed Firmware Update, hardware-based attestation with Microsoft PKI and Microsoft Secure Pairing, and network security including 802.1X, Wi-Fi WPA3, and proxy server support. The touch panel shall be CE marked, UL listed, and compliant with the RoHS directive. Warranty shall be three years. The touch panel shall be the Biamp Apprimo™ Touch 10 UCX-T.

APPRIMO TOUCH 10 UCX-T SPECIFICATIONS

Platform: Operating System: Microsoft Device Ecosystem Platform (MDEP) based on Android 15 UC Vendors: Microsoft Teams Rooms for Android Compatibility: Devio UCX 1000, Devio UCX 2000, Devio UCX 3000 Processor: Qualcomm Dragonwing QCS5430 Memory: 8 GB Display: Size: 10.1" diagonal IPS LCD Resolution: 1920 x 1200 Brightness: 380 cd/m², auto-adjusting Touch Screen: Capacitive touch, optically bonded with LCD, anti-fingerprint coating, diffuse texture Sensors: Ambient Light: Auto-brightness Ultrasonic: Ultrasonic beacon for Microsoft Teams Rooms proximity join Motion Detection: Wake system on motion Ports: USB-C Input: Content Sharing and BYOM Switch, USB-C DP 1.4a Alt Mode, 4K 30Hz USB-C Charging: 65W USB-C device charging when optional power supply is connected Power Input: Optional 100W USB-C power supply for Wi-Fi connections and 65W device charging Network and Wireless: Ethernet: Primary LAN, 100/1000, PoE+ Class 4 PD Wireless: Wi-Fi 6, 802.11ac Manageability: Biamp Workplace: Remote status monitoring, Biamp Launch Report Cards MDEP: Microsoft 365 Admin, Entra ID, Intune Microsoft Teams Rooms: Teams Admin Center, Teams Rooms Pro Management Portal Security: Platform: Secure Boot, Signed Firmware Update MDEP: Hardware-based attestation with Microsoft PKI, Microsoft Secure Pairing Network: 802.1X, Wi-Fi WPA 3, Proxy Server	Overall Dimensions: Height: 2.61 inches (66.3 mm) Width: 9.59 inches (243.6 mm) Depth: 6.09 inches (154.8 mm) Weight: TBD lbs (TBDkg) Angle: 20° Anti-Slip Base: Yes Power: PoE Input: PoE+ Class 4 powered device, 25.5W External Adapter: Optional USB-C 100W power supply for Wi-Fi or 65W USB-C device charging Power Consumption: < 25.5W, < 100W when charging external USB-C device Environmental: Ambient Temperature Range: 32-104° F (0-40° C) Humidity: 0-98%, non-condensing Altitude: 0-6,600 feet (0-2000 Meters) MSL Compliance: Certifications: FCC Part 15B (USA) Canada ICES-003 (A) / NMB-003 (A) CE marked (Europe) UL und C-UL listed (USA and Canada) RCM (Australia) RoHS Directive (Europe) Radio Equipment Directive (Europe) Warranty: Standard Warranty: 3 years Accessories: Optional Accessories: Apprimo Touch 10 UCX-TMA table mount accessory, Apprimo Touch 10 UCX-PSA power supply accessory
--	---

Biamp strives to improve its products on a continual basis. Specifications are therefore subject to change without notice.

Biamp and Apprimo are either trademarks or registered trademarks of Biamp Systems, LLC in the United States and other countries. Other product names referenced may be trademarks or registered marks of their respective owners and Biamp Systems is not affiliated with or sponsored by these companies.



A: 9300 S.W. Gemini Drive Beaverton, OR 97008 USA

T: +1 503.641.7287

W: www.biamp.com

rev.0926