INFOCUS JTOUCH SERIES 13 - IN7513

InFocus JTouch Series 13 - IN7513 - Google EDLA-Certified

Enhance your interactive experience with InFocus JTouch Series 13, our latest Google EDLA-certified interactive display. Seamlessly integrated with the Google ecosystem, the InFocus JTouch Series 13 delivers a high-performance, intuitive interactive experience with access to Google Mobile Services (GMS) and essential applications like Google Play Store.

Features

Safe and Easy NFC Login

Built-in new digital edge NFC provides quick access to user personal account. Access is secure, authenticated to prevent unauthorized access.

Well-being Safeguards

Special screen treatments including anti-microbial, anti-fingerprint, anti-glare, and certified low blue light to prioritize the user's well-being.

Array of 8 Microphones

Equipped with 8-Array microphones with noise cancellation, up to 10 meter far-field sound pickup, and voice enhancement to ensure everyone is clearly heard.

AI Camera

48MP 120° wide-angled and integrated with many AI features such as speaker tracking, sound source localization, gesture recognition and noise reduction to optimize video experience.

USB Type-C Single Cable Solution

Simplify your setup with USB Type-C cable connection for two-way data/audio/video transmission, two-way control function and delivers up to 65W power.

Display

Backlight	Direct LED (Wide Colour Gamut, Certified Low Blue Light, Certified Flicker-Free)

Glass Surface	Glass Surface - 3mm Anti-Glare, Anti-Fingerprint, Anti-Microbial 7H Tempered Glass
Bonding Technology	Zero Bonding
Aspect Ratio	16:9
Native Resolution	4K UHD 3840 × 2160
Display Colours (billion)	1.07
Contrast Ratio	1200:1
Dynamic Contrast Ratio	5000:1
Brightness (Maximum cd/m2)	450
Display Area (mm/inch)	1650 × 928 / 64.96 × 96.54
Viewing Angle (H–V°)	178 / 178
VESA-Mount MIS-F	600 × 400
Response Time (ms)	8
Display Lifetime Maximum (hours)	50000
Built-In Camera (MP)	48
Field of View (degrees)	120
Microphones	8
AI Camera Functionality	Speaker Tracking, Gesture Recognition, Sound Source Location, OSD Prompts, Noise Reduction
Pick-up Distance (meters)	10
Face Chip	Far Field Audio Up, Echo Cancellation
Frame Rate	30fps/MJPG, H.264/H.265 3840 × 2160, 2560 ×1440, 1920 x1080, 1280 × 720
Refresh Rate (Hz)	60
Audio (W)	Front Facing Speaker 16W x 2; Rear Facing Sub-Woofer 20W
Frame Material	Aluminium

Connectivity

Front Inputs	USB-C (Display Port IN, USB3.0, USB2.0, PD 15W) , 3x USB-A 3.0, HDMI 2.0 (IN1), NFC
Front Outputs	Touch USB-B 3.0
Left Inputs	3x HDMI (IN2, IN3, IN4) , Display Port , USB-C (Display Port IN, USB3.0, USB2.0, PD 65W), Public USB-A 3.0, Public USB-A 2.0 , Micro-SD card
Left Outputs	Touch USB-B 3.0
Bottom Inputs	MIC, RS232, Android USB-A 3.0
Bottom Outputs	Line, SPDIF, HDMI, USB-C (Display Port OUT, USB 3.0, PD 5W)
Bottom Networking	2x RJ-45 (LAN 1, LAN2)

Power

Power Supply	100 - 240V AC 60/50HZ
Power Consumption (W)	≤300
Power Consumption Standby (W)	≤0.5
Power Consumption Network Standby (W)	≤3.0

Touch System

Touch Technology	Infra-Red
Touch Points Maximum	40
Touch Resolution	32768 × 32768
Typical Response Time (ms)	5
Accuracy (mm)	+/- 1
Minimum Object Size Single Touch (mm)	1
Minimum Object Size Multi Touch (mm)	2

Embedded System

Operating System and Version	Android 13
System on Chip (SoC)	Rockchip RK3588
Central Processing Unit (CPU)	4x ARM Cortex-A76 2.4GHz + 4x ARM Cortex-A55 1.8 GHz
Graphics Processing Unit (GPU)	ARM Mali-G610 MC4
Neural Processing Unit (NPU)	6 TOPS
Random Access Memory (RAM)	8GB DDR4
Read Only Memory (ROM)	128GB EMMC
Supported Image Formats	JPG, JPEG, BMP, PNG
Supported Video Formats	MPEG1, MPEG2, MPEG4, H.263, H.264, MVC, AVS, AVS+, WMV3, VC1, Motion JPEG, VP8, VP9, RV30/RV40
Supported Audio Formats	MP1, MP2, MP3, EAC3, ACC-LC, HEAAC, FLAC
Wireless	Intel® Wi-Fi 6 2.4GHz/5GHz (802.11 a,b,g,n, ac, ax), Bluetooth 5.0
Supported Operating Systems	Windows, Linux, Chromium OS, Mac OS, Chrome OS, Android

General

Dimensions (L x W x H) (mm / in)	1717 × 92 × 1050 / 67.6 × 3.62 × 41.53
Shipping Dimensions (L x W x H) (mm / in)	1821 × 175 × 1140 / 71.70 × 6.89 × 44.88
Weight (kg / lb)	46.1 / 101.6
Shipping Weight (kg / lb)	55.4 / 122.1
Max Operating Altitude (meters / feet)	3000 / 9843
Security	PIN Code Lock & Timer, NFC
Operating Temperature (Celsius / Fahrenheit)	0 - 40 / 32 - 104
Storage Temperature (Celsius / Fahrenheit)	-10 - 45 / 14 - 113
Operating Humidity (%)	10 - 90 (RH non-condensing)

Storage Humidity (%)	5-90 (RH non-condensing)
Environmental	RoHS, Certified Low Blue Light, Certified Flicker-Free
Safety and Regulatory	CB, CE, cTUVus, EMC, FCC, UKCA
What's in the Box	x1 Remote, x2 Stylus, x1 NFC Comm Admin Card, x5 NFC User Card, x1 3m Touch USB-B Cable, x1 3m USB-A Cable, x1 VESA Wall-mount, x1 3m Power Cable (US), x1 3m Power Cable (EU), x1 3m HDMI Cable, x1 Simplified User Guide

Copyright © 2026, InFocus and its logo is a registered trademark of InFocus Corporation. Maxnerva Technology Services Limited is the licensee of the registered trademark. All other product names and company names used herein are for identification purposes only and may be trademarks or registered trademarks of their respective owners. Errors and omissions excepted; all specifications are subject to change without notice. All images are for representation purposes only and may be simulated.