

REACH

Effortless BYOD. Every room. Every time.



FEATURES

ONE CABLE. BYOD FOR THE WHOLE TABLE.

- BYOD across the room: Jabra Reach is a single cable that extends BYOD to the entire table.
- Compatible with all Jabra video room solutions: One USB-C connection works with all devices.*
- Seamlessly reliable: Jabra Reach delivers lossless audio, video and content, in any size room.

FAST, TIDY INSTALLATION

- Streamline setup: Quick and easy single-cable installation instead of multiple adapters and cables.
- Smart, professional finish: Sleek design fits behind the TV and under the table.
- Reduced complexity: With minimal cabling required, common failure points are removed.

EASY MANAGEMENT

- Centralised control: Manage devices across all rooms from a single platform with Jabra Plus Management.
- Secure and durable design: Tamperproof construction and concealed ports improve reliability and protect installations.
- Simplified operations: IT leads will experience reduced management and fewer day-to-day tickets.

SCALABLE FOR EVERY TYPE OF ROOM

- One accessory. Every space: Engineered to enhance BYOD across all room shapes and sizes.
- Standardized deployments: Modular components make it easy to configure different room types.
- Scale with your business: Predictable, scalable management for multi-room and multi-site rollouts.

SEAMLESS PLUG & PLAY

- Instant connectivity: Users simply connect a single USB-C cable into their laptop. Users can also charge during calls (power supply sold separately)¹
- Reliable performance: Lossless extension of audio, video and content, consistently and predictably.
- No drivers or software: No setup required, just true Plug & Play.

ONE SETUP FOR INSTALLERS. ONE SYSTEM FOR IT. ONE EXPERIENCE FOR USERS.

Technical Specifications

General info	Box contents **	Front of Room (FoR) box (RX) • Center of Room (CoR) box (TX) • USB C to USB C 3.2 gen 1 Cable (1.8m / 5.9 ft) • Magnetic cable home • 1 x USB A to USB C (1.2m / 3.9 ft)
	Packaging dimensions (WxHxD)	193.5 x 145 x 161 mm 7.63 x 5.72 x 6.35 in
	Main unit dimensions (WxHxD) - Front of Room (FoR Tx) Box (RX)	134 x 24 x 135 mm 5.28 x 0.94 x 5.31 in
	Main unit weight - Front of Room (FoR) Box (RX)	326 g 11.5 oz
	Main unit weight - Center of Room (CoR) Box (TX)	315 g 11.1 oz
	Package weight	1.2 kg 2.56 lbs
	Cable management	Yes
	Operating voltage	100-240V, 12V/2A
	System requirements	Windows (latest two versions), macOS (latest two versions), Chrome OS
	Verified peripheral devices *	PanaCast 40 VBS, PanaCast U30, PanaCast 50/55 VBS, PanaCast 50, Huddly IQ, Speak2 75
	Warranty	2 years
Video	Display resolution	Supports up to 4K60 4:4:4
	Content sharing	USB-C (DP-alt mode)
Security	Media encryption	HDCP supported, USB provided by VaaS partner
	Firmware update	Digitally signed and Encrypted (NIST SHA-256 bits, Public Key Hash)
Connectivity	Interfaces - Front of Room (FoR) Box (RX)	2x USB-A 2.0, 1x USB-C 2.0 (Device Management), 1x RJ45 To CoR (HDBaseT), 1x HDMI 2.0 (Output), 1x DC power in
	Interfaces - Center of Room (CoR) Box (TX)	1x USB-C (USB 2.0 + DP alt mode + PD), 1x RJ45 To FoR (HDBaseT), 1x USB-C (PD input only) 20v/100w Charge *Optional ¹
Software & Apps	Device management	Jabra Plus; Jabra web console for remote management via HTTPS; Jabra direct ²
Ease of use	Mounting options	Wall, Table, Display, Grommet mount for grommet hole ³
Extended info	Operating temperature	0°C to 35°C 32°F to 95°F
	Storage temperature	-20°C to 45°C -4°F to 113°F
	Maximum altitude	2000m 6561ft

Product type	SKU	Description
Products	8700-104	Jabra Reach
Accessories	14202-23	Jabra PanaCast 50 Power Supply
	14208-31	Jabra USB Cable for Evolve2 and Engage SE (USB-A to USB-C) - Black
	14208-50	Jabra HDMI Cable (1.83m/6ft)
	14307-62	Jabra Reach Grommet Mount
	14402-12	Jabra USB-C Active Cable (USB-C to USB-C) - 3.2 Gen 1 (5m)

A Cat6a cable (or higher) is required to support an extension of up to 100 metres/328 feet.

** SKU 8700-104 does not include a power supply. In order to use the Jabra Reach, a separate power supply (SKU 14202-23, which includes an India cord) must be purchased.

¹ Standard USB-C Power adapter to power end user laptop not included in the box and must be purchased separately.

² Jabra Plus, HTTPS supported for U30, P40/50/55 VBS. For PanaCast 50 and for other configurations, use Jabra Direct for Jabra Reach updates

³ Wall and table mounting: supports screws up to 4 mm in diameter, Display mounting on Vesa plate: supports M3 screws, Jabra screen mount: supports M5 screw

Jabra Reach Tech Sheet 28082026

Download the latest version of this document at:
public-uat.gnajabra.com/en-in/support

© 2026 GN Hearing A/S. All rights reserved.

Jabra® is a registered trademark of GN Hearing A/S.

The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by GN Hearing A/S is under license.

Specifications are subject to change without notice.