MAXHUB

# MAXHUB Wireless Screen Sharing Dongle WT15S

Instant Collaboration, Zero Hassle

### Share Your Screen in Stunning 4K

Crystal-clear 4K presentations, ultra-low latency for smooth, responsive, synced screen sharing.

### Plug and Play in 3 Seconds*

Simply plug the dongle into your laptop and start sharing within 3 seconds.

### Enterprise-Grade Security

AES 128-bit multi-layered encryption, dynamic key negotiation and multi-factor authentication for independent connection security.

*3 Seconds：Response time from dongle insertion to laptop screen projection readiness; USB-C: ≥3s, USB-A: ≥10s.

MAXHUB

# Built for the Modern Workplace

Instant Collaboration, Zero Hassle

### 1 Durable Cable and Adapter

- Over 20,000 bending tests for extended lifespan.
- Integrated USB adapter for seamless USB-C/USB-A switching.

### 2 Anti-Loss Design

Dedicated lanyard hole for secure mounting, effectively preventing misplacement

## Wireless Screen Sharing Dongle

| Interface | |
|---|---|
| USB Type-C | ×1 |
| USB Type-A (Adapter) | ×1 |

| Performance | |
|---|---|
| Wireless Connection Range (Max.) | 12 m / 39 ft |
| Supported Operating Systems | Windows 7/10/11, macOS 10.12 or later |
| Startup Time | ≥ 3s (USB-C), ≥ 10s (USB-A) |
| Disconnect Time | ≥ 5s |
| Transmission Latency (1080P) | ≥ 90 ms |
| Wireless Screen Sharing Resolution (Max.) | 3840×2160@30 Hz |
| Touchback Control | Supported |

| Indicator Light | | |
|---|---|---|
| Connecting to Endpoint | Flash White | The dongle is starting up |
| | Flash Blue | Pairing/Updating |
| | Solid Blue | Paired successfully |
| | Solid Red | Failed to pair |
| Connecting to Laptop | Flash White | Pairing |
| | Solid White | Paired successfully |
| | Solid Green | Sharing the screen |

| Wi-Fi | |
|---|---|
| Wi-Fi Standard | 802.11a/n/ac |
| Wi-Fi Frequency | 5G Hz |

| Power | |
|---|---|
| Power Supply | 5 V@500 mA |
| Power Consumption | ≤2.5 W |

| Physical Specification | |
|---|---|
| Dimension (L×H×D) | 182.5×15.4×76.1 mm |
| Shipping Dimension (L×H×D) | 1pcs: 196×28×110 mm |
| | 60pcs: 420×350×360 mm |
| Net Weight | 73 g |
| Gross Weight | 1pcs: 230 g |
| | 60pcs: 15.4 kg |

| Environment | |
|---|---|
| Operating Temperature | 0°C~40°C |
| Storage Temperature | -20°C~60°C |
| Operating Humidity | 10%~90%RH |
| Storage Humidity | 10%~90%RH |
| Altitude | Below 5000 meters |

Statement

Size and weight vary by configuration and manufacturing process, please refer to the actual product. The product images are for illustrative purposes only and may slightly differ in appearance, colour, size, etc. from the actual product. The description, illustrations, etc. in this document may subject to change in accordance with the latest product specification and performance. Should the above-mentioned change in the document become necessary, the document may be updated without written notice.