


Yealink CT200 Datasheet

Device Navigator



The CT200 is a powerful Device Navigator that enables seamless management and monitoring of room devices, including AVoIP, cameras, audio, and more. With advanced room control capabilities, such as routing AV signals and managing display power, it delivers an automated, tailored experience for any room configuration.

Key Features and Benefits

Efficient Management with Dual Network Ports

With two network ports, the Yealink CT200 enables the separation of management and device control, ensuring secure, efficient network traffic and better overall system performance.

Effortless Third-Party Integration via Open API

Yealink empowers seamless third-party device integration with its powerful Open API capabilities, enabling flexible and customized solutions.

Specifications

Parameter	Description
Installation Method	• Rack installation • Flat installation
Hardware Interface	• 1 × PoE port • 1 × RJ45 port • 1 × MGMT port

	• 1 × 12V/2A power supply port
Package Contents	• 1 × CT200 • 1 × 3 m Cat5e cable • 1 × 1.0 m USB 3.0 Type-C to Type-A Cable (for management port) • 1 × Power adapter (12V / 2A) • 1 × Mounting Kit (for wall, flat surface, or rack installation). Includes mounting ears, rack connection piece, and screws. • 1 × Quick start guide
Environmental Factors	• Operating humidity: 10 ~ 95 % • Operating temperature: -10 ~ +45 °C • Storage temperature: -30 ~ 70 °C
Power Supply	• Power consumption: ◦ Average: 2 W ◦ Peak: 3.5 W ◦ Standby: 1.7 W • Power Supply: ◦ Power Adapter: DC 12V/2A ◦ PoE: 802.3af
Dimensions and Weight (W × D × H)	• Giftbox size: 259 × 193 × 124 mm • Carton size: 635 × 265 × 209 mm • Dimensions: 216 × 160 × 36 mm • G.W/CTN: 9.252 kg • N.W/CTN: 8.530 kg • Weight: 1.46 kg • Quantity/carton: 5 pcs